The Aspen outdoor wall sconce creates an elegant elongated column of beautifully diffused light. The Aspen is available in four sizes (8", 15", 26", 36") to meet architectural scale; ideal for wayfinding and general outdoor illumination. The Aspen features energy-efficient, fully dimmable integrated LED lamping. Available in two finishes: Bronze and Charcoal.

### Outstanding protection against the elements:

- Powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized frosted acrylic lensing
- IP65 Rated

### **SPECIFICATIONS**

DELIVERED LUMENS	390
WATTS	15
VOLTAGE	Universal 120-277V, with integral transient 2.5kV surge protection (driver)
DIMMING	0-10, ELV
LIGHT DISTRIBUTION	Symmetric
MOUNTING OPTIONS	Wall
PERFORMANCE OPTIONS	In-Line Fuse / Surge Protector
CCT	2700K, 3000K
CRI	90+
COLOR BINNING	3 Step
BUG RATING	B0-U3-G1
DARK SKY	Non-compliant
WET LISTED	IP65
GENERAL LISTING	ETL
CALIFORNIA TITLE 24	Can be used to comply with CEC 2019 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.
START TEMP	-30°C
FIELD SERVICEABLE LED	Yes
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Powder Coat
LED LIFETIME	L70; >60,000 Hours
WARRANTY*	5 Years








ASPEN 8 shown in bronze

ORDERING INFORMATION

\* Visit techlighting.com for specific warranty limitations and details.

PRODUCT	CRI / CCT	LENGTH	LENS	FINISH	VOLTAGE	DISTRIBUTION	OPTIONS
700OWASP	<b>927</b> 90 CRI, 2700K <b>930</b> 90 CRI, 3000K	8 8"	<b>D</b> DIFFUSE	Z BRONZE H CHARCOAL	UNV 120V-277V UNIVERSAL	<b>S</b> SYMMETRIC	NONE  LF IN-LINE FUSE  SP SURGE PROTECTION  LFSP IN-LINE FUSE & SURGE PROTECTION




Aspen 8

## PHOTOMETRICS\*

\*For latest photometrics, please visit www.techlighting.com/OUTDOOR

#### ASPEN 8

Total Lumen Output: 390
Total Power: 15
Luminaire Efficacy: 26
Color Temp: 3000K
CRI: 90
BUG Rating: B0-U3-G1



# PROJECT INFO

FIXTURE TYPE & QUANTITY

JOB NAME & INFO

NOTES

TECH LIGHTING

Visual Comfort & Co.

**(T)** 

7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400