



THE **FLKs.4**


LU  ILLUMINAIRE



## FLKS.4


**Lighting at its finest.** The FLKS.4 features a sleek, low profile design with a 4-inch aperture and features Power Over Cable suspension. Designed with versatility in mind, an optional in-field rotational hub allows the connection of up to four FLKS.4 luminaires for maximum flexibility. The FLKS.4 utilizes anodolic light guide technology, minimizing light glare for optimal performance.

### STYLES



**STANDARD FINISHES**  
**Black, White & Silver**

LUXILLUMINAIRE.COM



### PENDANT DIRECT

lm/w  
**Up to 106**

UGR  
**< 19**

Distribution  
**100**

Hub Rotation  
**15° increments**  
**From 90° to 180°**

Configurations  
**2, 3, 4, 5 & 6 ft Individual Units**  
**Custom configurations**  
**made up with any of the**  
**above units.**

### OPTICS



LAMBERTAIN  
DIRECT



LAMBERTAIN  
DIRECT  
**EXTREME BAT WING  
INDIRECT**



### PENDANT DIRECT/INDIRECT

lm/w  
**Up to 119**

UGR  
**< 19**

Distribution  
**37/63, 52/48, 47/53**

Hub Rotation  
**15° increments**  
**From 90° to 180°**

Configurations  
**2, 3, 4, 5 & 6 ft Individual Units**  
**Custom configurations**  
**made up with any of the**  
**above units.**



LAMBERTAIN  
DIRECT  
**BAT WING  
INDIRECT**



LAMBERTAIN  
DIRECT  
**BAT WING  
INDIRECT**