

- Available in LED & Incandescent
- Fade & Rust Resistant Composite Construction
- Black, White, or Bronze
- Optional Photocell
- UL Listed for Wet Locations



**EXAMPLE # AE145-I60-ZF-LWE**

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
<b>AE145</b>	<b>EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR</b>	<b>B-Black W-White Z-Bronze</b>	<b>ACRYLIC C-Clear F-Glare Free Frost</b>	<b>P-Photocell</b>
	<b>LE800-13W Power Input CRI 80 (TYP) &gt;65 Lumens Per Watt**</b>	<b>W-1140lm 3000K C-1280lm 4000K</b>		
	<b>INCANDESCENT, MEDIUM BASE, 120V I60-1 X 60W Max</b>	<b>B-Black W-White Z-Bronze</b>	<b>ACRYLIC C-Clear F-Glare Free Frost</b>	<b>P-Photocell LED LAMP, 3 YR WARRANTY, DIMMABLE, ENERGY STAR LWE-A19/E26, 3000K LCE-A19/E26, 4000K</b>