


- Available in LED, Incandescent & GU24
- Molded of Durable Non-Corrosive UV Resistant Resins
- Wall Mount Only
- UL Listed for Damp Locations



EXAMPLE # AEL37-I60-BW-PLWE

SERIES #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
AEL37	LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR	B-Black	ACRYLIC W-White	P-Photocell
	LE800-13W Power Input W-900lm 3000K CRI 80 (TYP) C-1000lm 4000K >65 Lumens Per Watt**			
	INCANDESCENT, MEDIUM BASE, 120V I60-1 X 60W Max	B-Black	ACRYLIC W-White	P-Photocell LED LAMP, 3 YEAR WARRANTY DIMMABLE, ENERGY STAR LWE-A19/E26, 2700K LCE-A19/E26, 4000K
GU24 BASE, 120V G13-1 X 13W G18-1 X 18W G23-1 X 23W	B-Black	ACRYLIC W-White	P-Photocell L-CFL, 2700K	

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE

AEL -- Advantage Environmental Lighting

Address: 917 West Mayfield, Suite 103
Arlington, TX 76015
Phone: 817-468-3591
Email: info@aelnow.com

Catalog #	
Project	
Date	
Type	

Specifications are subject to change without notice.