

## AE52

### Wall Sconce

#### Housing

Die-formed Cold-rolled Steel

Finish Option: -62 Satin Nickel -30 Oil Rubbed Bronze

#### Optical

Shade: High Transmission Glass Creates Excellent Light Distribution and Uniformity

LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

#### Electrical

High Power Factor, Low THD

#### Lamp


LED Type: Integrate LED Module , 3000K LED. More Color Temperature Option 3500K, 4000K, 5000K. GU24 Type: CFL Bulb, 2700K or 4000K, 9W LED Bulb, 3000K or 4000K

#### Certification

UL/cUL, ETL/cETL Listed, Suitable for Damp Locations

#### Warranty

5 Years Limited Warranty on Driver and LED



#### LED Type

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Finish/Shade	Dimension (W x H X D)	Energy Star
AE52	120V	14W	3000K 3500K 4000K 5000K	>80	1050	S. Nickel / Frosted glass	8.7" x 10.2" x 3.8"	Yes

#### GU24 Type

Model	Input Voltage	Lamp	Finish	Shade	Dimension (W x H X D)	Energy Star
AE52-123	120V	1 x 23W GU24	Satin Nickel	Frosted Glass	8.7" x 10.2" x 3.8"	--
AE52-213	120V	2 x 13W GU24	Satin Nickel	Frosted Glass	8.7" x 10.2" x 3.8"	---