

**Features**

**Housing**

Die-formed Cold-rolled Steel  
Finish Option: Satin Nickel

**Optical**

Shade: High Transmission Acrylic Create Excellent Light Distribution and Uniformity LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light.

**CCT**

Color temp adjustable in Field: optional simple flip switch located on the LED board for desired CCT (3000K-4000K).

**Electrical**

High Power Factor, Low THD

**Lamp**

LED Type: Built-in (Color Temperature Option – 3000K, 4000K)

**Certification**

UL/cUL, ETL/cETL Listed, Energy Star

**Warranty**

5 Years Warranty on Driver and LED Module



STANDARD

OPTIONAL



Model	Input Voltage	Input Wattage	LED CT / CRI	Lumen (TYP)	Finish	Dimension (L x W x E)	Energy Star
AE5524-3000K	120V	19W	3000K / 80	1420	Satin Nickel	25.5" x 4.8" x 4.5"	Yes
AE5524-4000K	120V	19W	4000K / 80	1500	Satin Nickel	25.5" x 4.8" x 4.5"	Yes
AE5539-3000K	120V ~ 277V	23W	3000K / 80	1800	Satin Nickel	37.5" x 4.8" x 4.5"	Yes
AE5539-4000K	120V ~ 277V	23W	4000K / 80	1900	Satin Nickel	37.5" x 4.8" x 4.5"	Yes
AE5554-3000K	120V ~ 277V	38W	3000K / 80	3000	Satin Nickel	49.3" x 4.8" x 4.5"	Yes
AE5554-4000K	120V ~ 277V	38W	4000K / 80	3160	Satin Nickel	49.3" x 4.8" x 4.5"	Yes

Options
CS CCT Switch