

BAU

LED Prison Grade Surface Ceiling Mount



STANDARD

OPTIONAL



SPECIFICATIONS

DESCRIPTION

The BAU is an impact resistant and vandal proof LED surface mount fixture designed to maintain

CONSTRUCTION

18-gauge cold roll steel housing. White TGIC polyester powdercoat with a 5 stage treatment provides long lasting, protective finish. Consult factory for additional color options. Torx® head screws with center pin fasteners secure the housing to the baseplate.

ELECTRICAL SYSTEM

Electronic driver 0-10V 1% dimming standard. Long-life LED system rated for >100K hours (L70 @ 45°C). Complies with federal energy efficiency standards. 3000K, 3500K, 4000K, and 5000K color temperatures available, with a CRI >82.

OPTICAL SYSTEM

One piece Injection molded polycarbonate drop lens coated with a proprietary treatment to retard yellowing in ultraviolet environments provides superior light dispersion and luminaire protection.

LISTINGS

UL/cUL Listed. Manufactured in the USA, BAA compliant.

MOUNTING

Fixture provided with mounting holes on the housing. Optional knockouts on one or two sides for continuous run mounting.

GASKET

Closed cell gasket seals the lens and housing to the mounting surface.

WARRANTY

5 - Year Limited Warranty. Complete warranty and terms located at: www.aelnow.com/warranty

Output	Lumens	W	L70 @45°C (hrs)
S	2224	16	>100,000
M	2780	20	>100,000
H	3475	25	>100,000
VH	4865	35	>100,000

* Delivered Lumens shown were tested with 4000K LEDs

ORDERING INFORMATION

Example:BAU40MM

Series	CCT	Output	Voltage	Options
BAU	30	3000K	M Multi-Volt (120/277V)	12EBL 1200 Lumen Emergency Ballast
	35	3500K		90 90 CRI
	40	4000K		FH Fuse & Holder
	50	5000K		KO1 KO on One Side KO2 KO on Two Sides

LINE ART

