

# LDAWW

Angled Surface Mount  
Wall Wash LED Luminaire



STANDARD

OPTIONAL



## PRODUCT SPECIFICATIONS

### DESCRIPTION

The LDAWW is an architecturally designed Surface Mount Direct Steel LED Luminaire that is classically styled and fit for any interior. It is available for continuous run mounting.

### APPLICATIONS

The LDAWW LED Luminaires were designed to be high quality, energy efficient LED fixtures for use in commercial applications, offices, hotel lobbies, museums, government facilities, schools, and public areas.

### CONSTRUCTION

The fixture is constructed of a 1.4375" wide heavy gauge steel body. The LDAW is available in any run length withing 2' increments. Heavy duty housing crimped along sides for extra rigidity and straight alignment.

### OPTICAL SYSTEM

High output LED's available in 3000K, 3500K, 4000K, and 5000K. CRI>82. Linear ribbed acrylic lens. White polyester polymer finish with a high reflectivity.

### ELECTRICAL SYSTEM

Electronic drivers are available for 120/277V applications. Long-life LED system rated for >100,000 life hours (L70@25° C). Metal gear tray for internal LED driver. Complies with Federal Energy Efficiency Standards.

### MOUNTING

This fixture is designed to be surface mounted. Continuous run available.

### LISTINGS

Independently tested to IESNA LM-79 and LM-80 specifications. UL and cUL Listed.

### WARRANTY

5-Year Limited Warranty. Complete warranty and terms located at [www.aelnow.com/warranty](http://www.aelnow.com/warranty)


## ORDERING INFORMATION

Example: LDAWW40MSMW8

Options: 13EBL, WH58

SERIES	COLOR TEMP	OUTPUT	LENS	VOLTAGE	FINISH	ROW LENGTH (IN FEET)	OPTIONS	WIRING HARNESS
LDAWW	30 3000K 35 3500K 40 4000K 50 5000K	S Standard M Medium H High	A12 .100 #12 Acrylic S Satin Lens	M 120/277V (Multi-Volt)	W White SP Special	2 2 Feet 3 3 Feet 4 4 Feet 5 5 Feet 6 6 Feet 7 7 Feet 8 8 Feet XX Length in Ft	13EBL 1300 Lumen Emergency Ballast FW Flex Whip Cable 6' 45 45 Degree 90 90 Degree	WH34 3-Wire 4 Feet WH44 4-Wire 4 Feet WH54 5-Wire 4 Feet WH38 3-Wire 8 Feet WH48 4-Wire 8 Feet WH58 5-Wire 8 Feet

\*\*PLEASE NOTE: Contact Factory for Special Applications, including Ceiling-to-Wall\*\*

**FIXTURE DIMENSIONS**

**ROW CONFIGURATIONS**
**LED SYSTEM DATA**

Output	Delivered Lumens Per Foot	System Wattage Per Foot	CRI	LPW
Standard	506 Lm/Ft	3.3	82	148
Medium	709 Lm/Ft	5.1	82	139
High	1,468 Lm/Ft	10.3	82	143

*Contact Factory For Additional Lumen Packages*

**ENERGY AND PERFORMANCE DATA**

Input Voltage	120/277 VAC
Standard Dimming Control	0-10V
CCT	3000, 3500, 4000, 5000 Kelvin
CRI	82 (minimum)
Life Time Rating	100,000 hrs at L70
Input Frequency	50/60Hz
Power Factor	>0.9
Operating Temp	Low Ambient -20°C/ High Ambient 50°C

Quick Reference Output Guide Standard		
Length	Lumens	Wattage
2 Foot	1012	6.6
3 Foot	1518	15.3
4 Foot	2024	41.2
6 Foot	3036	19.8
8 Foot	4048	26.4

Quick Reference Output Guide Medium		
Length	Lumens	Wattage
2 Foot	1418	10.2
3 Foot	2127	15.3
4 Foot	2836	20.4
6 Foot	4254	30.6
8 Foot	5672	40.8

Quick Reference Output Guide High		
Length	Lumens	Wattage
2 Foot	2936	20.6
3 Foot	4404	30.9
4 Foot	5872	41.2
6 Foot	8808	61.8
8 Foot	11744	82.4