



LWV02

LED Wall / Vanity Luminaire



STANDARD

OPTIONAL



PRODUCT SPECIFICATIONS

DESCRIPTION

The LWV02 Series is a high quality Wall/Vanity LED Luminaire.

APPLICATIONS

The LWV02 series of LED Wall/Vanity fixtures are designed to be high quality, energy efficient LED fixtures for use in corridors, stairwells, bathrooms, and other spaces.

CONSTRUCTION

The fixture is constructed of a structurally embossed, heavy gauge, cold rolled steel. Baked white enamel finish or bright anodized aluminum finish. Custom colors available.

OPTICAL SYSTEM

Smooth Ribbed White Acrylic diffuser hides the appearance of the LEDs and offers excellent light transmission.

ELECTRICAL SYSTEM

Electronic driver 0-10V standard. Other driver options available, including Lutron. Long-life LED system rated for >100K hours (L70 @ 45°C). Complies with federal energy efficiency standards

MOUNTING

The LWV02 Series is designed for surface mounting on either a wall or ceiling.

LISTINGS

UL and cUL Listed. Damp location rated.

WARRANTY

5-Year Limited Warranty. Complete warranty and terms located at www.aelnow.com/warranty.

ORDERING INFORMATION

Example: LWV0240MLSWMW4

SERIES	COLOR TEMP		OUTPUT		DIFFUSER		VOLTAGE		COLOR		FIXTURE LENGTH	
LWV02	30	3000K	SL	Standard Low	SW	Smooth Ribbed White	M	Multi-Volt (120-277VAC)	W	White	2	2'
	35	3500K	ML	Medium Low					BAA	Bright Anodized Aluminum	4	4'
	40	4000K	HL	High Low					SP	Custom		
	50	5000K	SM	Standard Medium								
			MM	Medium Medium								

DRIVER OPTIONS		OPTIONS	
BLANK	0-10V Dimming Driver (included standard)	8EBLRM	8W Remote Mounted Emergency
CD1	0-10V 1% to Off Dimming Driver	PC	Pull Chain
CD5	0-10V 5% to Off Dimming Driver	CO	Convenience Outlet
EDN	Electronic Driver Non-Dimming	LWV02WG	Wire Guard
FLDD	Fifth Light Dali, Dimming	GFCI	Ground Fault Circuit Interruptor
LDE1	Lutron Hi-lume 1% EcoSystem LED driver with Soft-on, Fade-to-Black dimming technology	VDO	Lutron Vive Integral RF controller with daylight and occupancy sensing Lutron Vive Attached RF fixture controller for 0-10V drivers
LDE5	Lutron LDE5 5-Series Ecosystem 5% Dimming	FCJS0	

Output	Delivered Lumens	System Wattage	L70 @45°C (hrs)
SL	4650	33	>100K
ML	7974	57	>100K
HL	11150	80	>100K
SM	12040	86	>100K
MM	13016	93	>100K

Approximate Color Temperature Multiplier	
5000K	1.03
4000K	1
3500K	0.97
3000K	0.94
2700K	0.91

FIXTURE DIMENSIONS

