

Alphabet Of Light Mini Z wall 3000K

1215Z00A

SPECIFICATIONS



Design By
BJARKE INGELS GROUP

Collection

Design



Colors & Finishes

- ☐ White
- ☒ Brushed Anodized (support pins)

Materials

- Illuminated tubes in opaque injection molded PMMA
- Support pins in brushed aluminum

Specifications


Delivered lumens	1027lm
Light output ratio	103lm/W
Power consumption	10W
Led type	10W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	102000Hrs
Control type	Dimmable**
Input Voltage	24VDC
Driver	Remote power supply (sold separately)

*Integrated light source **With dimmable power supply

Features & Accessories

- 360° light emission
- Positioning template included
- Remote power supply 24Vdc 1x85W dimmable 0-10V galvanized(DEOW18508D1U)
- Remote power supply 24Vdc 2x85W dimmable 0-10V galvanized(DEOW28508D1U)
- Remote power supply 24Vdc 3x85W dimmable 0-10V galvanized(DEOW38508D1U)

Dimensions




Packaging

1 Box

1 x 18-3/16" x 17-13/16" x 5-5/8" / 0 lbs - 46 cm x 45 cm x 14 cm / 0 kg

Light distribution

Diffused



Red = Max Cd. Through Vertical plane
Blue = Max Cd. Through Horizontal plane

Luminaire weight

0 lbs / 0 kg

Warranty