LL1101



Design By

BJARKE INGELS GROUP

Collection -

Design



Colors & Finishes =

1
White

Materials =

- Illuminated tubes in opaque injection molded PMMA
- Trim in thermoplastic
- Frame in steel with powder coated finish

Specifications —


Delivered lumens	2400lm
Light output ratio	73lm/W
Power consumption	33W
Led type	33W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>95
Life expectancy	36000Hrs
Control type	N/A
Input Voltage	24VDC
Driver	Remote power supply (sold separately)

^{*}Integrated light source

Features & Accessories =

- Seamlessly integrates with the ceiling
- Patented optical unit
- Flexible tube of light let's you create your own design by changing the spacing

Dimensions -




*Not visible after installation

Light distribution =

Diffused

Luminaire weight —

8.62 lbs / 3.91 kg



Warranty =

Red = Max Cd. Through Vertical plane
Blue = Max Cd. Through Horizontal plane

Packaging =

2 Boxes

1 x 32" x 32" x 6-3/8" / 15.43 lbs - 81 cm x 81 cm x 16 cm / 7 kg

1 x 7-3/16" x 7-3/16" x 4-13/16" / 1.46 lbs - 18 cm x 18 cm x 12 cm / .66 kg

