

Cariddi wall/ceiling/floor 28W 40° 4000K anthracite

SPECIFICATIONS

T418640N08



Design By

Ernesto Gismondi

Collection

Outdoor



Specifications

| | |
|------------------------------------|-----------------------|
| Delivered lumens | 1571lm |
| Light output ratio | 56.11lm/W |
| Power consumption | 28W |
| Led type | 27W C.O.B.* |
| CCT (Correlated Color Temperature) | 4000K |
| CRI (Color Rendering Index) | >80 |
| Life expectancy | 50000Hrs |
| Control type | On/Off |
| Input Voltage | 120-277V |
| Driver | ROAL - 1 x RSLD035-12 |
| BUG Rating | B2-U0-G0 |

Colors & Finishes

■ Anthracite grey


Materials

- Body in aluminum
- Silicon-sealed silk-screened tempered glass
- Optical unit made of a PMMA lens and an anodized aluminum reflector

Features & Accessories

- Consists of an adjustable lighting unit and terminal board
- Rotation on base +/-180°, body tilting on bracket +/-130°, allowing accurate adjustment
- Positioning is maintained by means of locking dowels
- Electronic driver integrated

Dimensions



Packaging

1 Box


1 x 20" x 13-3/8" x 14-3/8" / 11.58 lbs - 50.7 cm x 33.7 cm x 36.3 cm / 5.252 kg

Light distribution

Direct

Luminaire weight

8.26 lbs / 3.75 kg



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

Warranty

5 year limited warranty