Cariddi wall/ceiling/floor 28W 40° 3000K anthracite

SPECIFICATIONS



• Silicon-sealed silk-screened tempered glass

Colors & Finishes

Anthracite grey

• Body in aluminum

Design By Ernesto Gismondi

Collection =



Specifications = **Delivered lumens** 1468lm Light output ratio 52.43lm/W Power consumption 28W 27W C.O.B.* Led type CCT (Correlated Color Temperature) 3000K CRI (Color Rendering Index) >80 Life expectancy 50000Hrs Control type On/Off 120-277V Input Voltage ROAL - 1 x RSLD035-12 Driver **BUG Rating** B2-U0-G0

Features & Accessories


• Consists of an adjustable lighting unit and terminal board

• Rotation on base +/-180°, body tilting on bracket +/-130°, allowing accurate adjustment

• Positioning is maintained by means of locking dowels


• Electronic driver integrated

Dimensions =



Light distribution =

Direct



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane Luminaire weight 8.26 lbs / 3.75 kg

Warranty 5 year limited warranty

• Optical unit made of a PMMA lens and an anodized aluminum reflector

Packaging =

1 Box

1 x 20" x 13-3/8" x 14-3/8" / 11.58 lbs - 50.7 cm x 33.7 cm x 36.3 cm / 5.252 kg

last updated: 2021-06-01

We reserve the right to change specifications of our products. For the latest product information please visit www.artemide.net

