


**STANDARD FINISHES**  
Black, White, & Silver



UP TO 126 lm/W PERFORMANCE				
INDIRECT LIGHT				
DIRECT LIGHT	375 lm/ft	500 lm/ft	750 lm/ft	1000 lm/ft
375 lm/ft	6.28	7.10	9.00	11.03
500 lm/ft	7.45	8.30	10.20	12.20
750 lm/ft	9.93	10.75	12.65	14.68
1000 lm/ft	12.45	13.28	15.18	17.20
1250 lm/ft	13.03	13.93	15.60	17.55

Performance based on 4-foot luminaire at 4.000K @ 25-degrees C

WATTS PER FOOT

LIGHT LOSS FACTOR		
CCT	CRI	%
4000K	84+	100%
3500K	84+	97.1%
3000K	84+	95.7%
2700K	84+	94.1%
4000K	92+	88.9%
3500K	92+	85.5%
3000K	92+	83.8%
2700K	92+	82.4%

## ORDER GUIDE

ARX.4 - W - DI

A

B

C

D

E

F

G

H

I

J

K (Multiple Selections)

EXAMPLE  
ARX.4 - W - DI | 500 | 500 | 6 | 40K | 8 | 2 | UNV | S1 | W

A. MODEL	B. DIRECT DISTRIBUTION			C. INDIRECT DISTRIBUTION		D. LENGTH		E. COLOR TEMPERATURE	
ARX.4 - W - DI	375	375 lm/ft	375	375	375 lm/ft	3	3 ft (36 in)	27K	2700K
	500	500 lm/ft	500	500	500 lm/ft	4	4 ft (48 in)	30K	3000K
	750	750 lm/ft	750	750	750 lm/ft	5	5 ft (60 in)	35K	3500K
	1000	1000 lm/ft	1000	1000	1000 lm/ft	6	6 ft (72 in)	40K	4000K
	1250	Custom lm/ft	XXX	XXX	Custom lm/ft	7	7 ft (84 in)		
	XXX					8	8 ft (96 in)		
						XXX	System Run		

F. CRI		G. CIRCUIT		H. VOLTAGE		I. DRIVER			
8	80+CRI	1	1 - Circuit	UNV	120 - 277v	S1	1% Dimming (0-10v)	DALI	DALI 2.0 Compatible
9	90+CRI	2	2 - Circuit	347	347v	LDE1	Lutron Hi-Lume 1% Fade to Black 0.1% EldoLED 1% Dexas		
						ELO			
						DXL			

Consult factory for outputs between min and max.		Consult factory for outputs between min and max.							
90 CRI option has an R9 value greater than 60.		347 may not be available in all configurations.		AWN-R-W, AWNR-B, VDO, VRF, SPD, & CLM options supplied with DXL driver standard.					

## OPTIONS

J. FINISH	K. CONTROLS & FACTORY OPTIONS		
W White	<input type="checkbox"/> NONE Leave Blank	SPD Osram SensiLUM Daylight/Harvest/Occ	<input type="checkbox"/> EB Emergency Battery (10 - Watt)
B Black	<input type="checkbox"/> AWNR-W Lutron Athena Wireless Node (RF-only) in White	CLM Osram Connecting Light Module (CLM)	<input type="checkbox"/> EC Emergency Circuit
S Silver	<input type="checkbox"/> AWNR-B Lutron Athena Wireless Node (RF-only) in Black	DAY Wattstopper Daylight Sensor (FD-301)	NL Night Light Circuit
CC Custom Colors	<input type="checkbox"/> VDO Lutron Vive (RF/Daylight/Occ)	OCC Wattstopper Occ Sensor (FS-205v2)	FO Flat Open End Plate
	<input type="checkbox"/> VRF Lutron Vive RF Fixture Control	DOC Enlighted Daylight/Harvesting Occ (SU-5E-01)	FC Flat Closed End Plate

Consult factory for custom colors.

AWN-R-W, AWNR-B, VDO, VRF, SPD, & CLM options supplied with DXL driver standard.  
EB option only available for lengths 4ft or greater.  
Sculpted end cap is standard.  
May choose more than one option in this category.

## LIGHT SOURCE

Long life name brand LED chips and boards to ensure the highest of quality while providing even and smooth illumination throughout our luminaires.

Our luminaires are available in 2700K, 3000K, 3500K and 4000K color temperature.

Optional 80CRI or 90CRI available in all CCT options.

## LUMEN MAINTENANCE

The projected lumen maintenance of the name brand mid-powered LED's are projected to maintain 80% (L80) of their initial output for +80,000 hours.

## CONSTRUCTION

The housings are constructed of (6063T5) extruded aluminum. Our internal joiner system is designed to the highest of standards to ensure our precision cut housings align and fit tightly without light leak. Our precision fitting end caps are constructed out of die cast aluminum.

## FINISH

Polyester powder, low gloss textured paint finish applied after a multi-stage pretreatment. Standard luminaire finishes include white, silver, and black. Custom color options are available. (Consult Factory).

## OPTICS

Curved reflector system.

## DRIVERS

All of our luminaires come standard with 1% dimming and THD <20% utilizing 0-10v constant current protocol. 120v/277v is standard with the option of 347v. Driver ambient operating temperature -30°C to +50°C.

## EMERGENCY

An integral factory installed 10 watt emergency battery pack. Emergency circuit and Night Light circuit options are available.

## LUMINAIRE LENGTH

Our ARX.4 Pendant Direct/Indirect luminaire series are available in 2', 3', 4', 5', 6', 7' and 8' individual lengths or continuous row configurations. Continuous row configurations are joined together on-site utilizing the joiner kits provided.



CONTINUOUS RUN ORDER GUIDES

Please use the following run guides for fixture ordering. If your product will require a submittal, our in-house Application Engineering Team will work closely with you on your project.

ALUMINUM PRODUCT ORDER GUIDE	
RUN LENGTH (ft)	RUN CONFIGURATION - SECTION LENGTHS
9	6' + 3'
10	6' + 4'
11	6' + 5'
12	6' + 6'
13	6' + 7'
14	8' + 6'
15	8' + 7'
16	8' + 8'
17	6' + 5' + 6'
18	6' + 6' + 6'
19	6' + 7' + 6'
20	8' + 4' + 8'
21	8' + 5' + 8'
22	8' + 6' + 8'
23	8' + 7' + 8'
24	8' + 8' + 8'
25	5' + 8' + 8' + 4'
26	4' + 6' + 6' + 6' + 4'
27	6' + 8' + 8' + 5'
28	6' + 8' + 8' + 6'
29	7' + 8' + 8' + 6'

\*Standard Run Configurations Shown, Consult Factory for Custom Configurations.

ALUMINUM PRODUCT ORDER GUIDE	
RUN LENGTH (ft)	RUN CONFIGURATION - SECTION LENGTHS
30	6' + 6' + 6' + 6' + 6'
31	6' + 6' + 7' + 6' + 6'
32	8' + 8' + 8' + 8'
33	5' + 8' + 8' + 8' + 4'
34	6' + 8' + 8' + 8' + 4'
35	6' + 8' + 8' + 8' + 5'
36	6' + 8' + 8' + 8' + 6'
37	8' + 8' + 5' + 8' + 8'
38	8' + 8' + 6' + 8' + 8'
39	8' + 8' + 7' + 8' + 8'
40	8' + 8' + 8' + 8' + 8'
41	5' + 8' + 8' + 8' + 8' + 4'
42	6' + 8' + 8' + 8' + 8' + 4'
43	6' + 8' + 8' + 8' + 8' + 5'
44	6' + 8' + 8' + 8' + 8' + 6'
45	7' + 8' + 8' + 8' + 8' + 6'
46	3' + 8' + 8' + 8' + 8' + 8' + 3'
47	4' + 8' + 8' + 8' + 8' + 8' + 3'
48	8' + 8' + 8' + 8' + 8' + 8'
49	5' + 8' + 8' + 8' + 8' + 8' + 4'
50	6' + 8' + 8' + 8' + 8' + 8' + 4'

\*Standard Run Configurations Shown, Consult Factory for Custom Configurations.

