

Project		Catalog #		Type	
Prepared by		Notes		Date	



## AtLite

### XLA2, XLN2

The XL exit is a New York City approved, architectural grade die cast, UL 924 code compliant product designed to operate for a minimum of 90 minutes during a power outage.

#### Typical Applications

Office • Education • Healthcare • Hospitality • Retail


#### Interactive Menu

- Order Information page 2
- Product Warranty

#### Product Certification



### Dimensional and Mounting Details



## Order Information

SAMPLE ORDER NUMBER: **XLN28DR2CESTPS**

Series	Letter Size	Housing	Letter Colors	Number of Faces	Housing Color	Options	Accessories
<b>XLA2</b> =AC Only <b>XLN2</b> =self powered	8-8"1	D=Die Cast	R=Red	<b>1ES</b> =One Face <b>2ES</b> =Two Faces	_=silver & black <b>WH</b> =white	_=none <b>TPS</b> =tamper proof screws	<b>GXB</b> =Wire Guard, Wall Mount, AC-Only Exit <b>GXBW</b> =Wire Guard, Wall Mount, Self Powered Exit <b>E</b> =end mount
Notes: 1. NYC Code Compliant with 8" letters only.							

## Product Specifications

### Electronic

- Dual-voltage input 120/277 VAC, 60Hz
- Solid-state circuitry (no mechanical relay is used)
- Constant-current charger
- Sealed, maintenance-free nickel cadmium battery

- Durable die-cast aluminum housing and faceplate
- Contemporary styled, soft-corner design
- Brushed aluminum or white finish
- Easily removed, changeable directional chevrons
- Low-profile mounting canopy included

### Code Compliance

- UL 924 Listed
- NFPA 101 Compliant
- NYC Code Compliant

### Warranty

- 5 year product warranty
- 7 year pro-rated battery warranty