



LED Mini Lamps



SLBP250L

Description: GY6.35 Bi-Pin Base LED

- 2.5 Watts, 9 - 20 Volt operating range
- 250 Lumen, Color Temp. 2750°K
- IP67 Rated, 25,000 Hours
- Can be used with CCH5CB (with Bi-Pin Socket) & CCH5LED1 (original non-integrated with Bi-Pin Socket)



SLSCB250L

Description: Single Contact Bayonet LED

- 2.5 Watts, 9 - 20 Volt operating range
- 250 Lumen, Color Temp. 2750°K
- IP67 Rated, 25,000 Hours
- Can be used with the following CAST fixtures manufactured with a SCB Socket: CCH5CB, CCH5LED1, Classic Path Lights, CNL1CB, & CDL1CB *Note: These fixtures were generally manufactured before July 2007



SL921T5200L

Description: 921 T5 Wedge Base LED

- 2.5 Watts, 9 - 15 Volt operating range
- 200 Lumen, Color Temp. 2750°K
- IP67 Rated, 25,000 Hours
- Can be used with CDL1CB, CDL2CB, CNL1CB, CEWL5CB & CEWL6CB



SL3156250L

Description: 3156 S8 Wedge Base LED

- 2.5 Watts, 9 - 20 Volt operating range
- 250 Lumen, Color Temp. 2750°K
- IP67 Rated, 25,000 Hours
- Can be used with Classic Path Lights with an S8 Wedge Base Socket

Limited 5 Year Warranty