




LAMP GUIDE

Mini LED Lamps



SLBP250L

Description:

- GY6.35 Bi-Pin Base LED
- 2.5 Watts, 9 - 20 Volt operating range
 - 250 Lumen, Color Temp. 2750°K
 - IP67 Rated, 25,000 Hrs.

Can be used with these Products:



Source Path/ Area Lights
(SAL100, SAL150, SALSTEM12, SALSTEM18)
*all pieces sold separately



CAST LANDSCAPE
Classic Mini China Hat
CCH5CB (with Bi-Pin Socket)
CCH5LED1 (original non-integrated)



SLSCB250L

Description:

- Single Contact Bayonet LED
- 2.5 Watts, 9 - 20 Volt operating range
 - 250 Lumen, Color Temp. 2750°K
 - IP67 Rated, 25,000 Hrs.


Can be used with these Products:

CAST LANDSCAPE



Classic Mini China Hat
CCH5CB (with SCB Socket)
CCH5LED1 (original non-integrated)

Classic Path Lights, Niche Light, & Deck Light
CCH***, CMU***, CNO***, CNL1CB, & CDL1CB
Manufactured Before July 2007



SL3156250L

Description:

- 3156 S8 Wedge Base LED
- 2.5 Watts, 9 - 20 Volt operating range
 - 250 Lumen, Color Temp. 2750°K
 - IP67 Rated, 25,000 Hrs.

Can be used with these Products:

CAST LANDSCAPE



Classic Path Lights
CCH13CB, CCH1CB, CCH2CB, CMU13CB, CMU1CB, CMU2CB, CNO13CB, CNO1CB, CSA1CB
Manufactured After July 2007



SL921T5200L

Description:

- 921 T5 Wedge Base LED
- 2.5 Watts, 9 - 15 Volt operating range
 - 200 Lumen, Color Temp. 2750°K
 - IP67 Rated, 25,000 Hrs.

Can be used with these Products:

CAST LANDSCAPE



Classic Deck, Niche, & Engineered Wall Lights
CDL1CB, CDL2CB, CNL1CB, CEWL5CB, & CEWL6CB



LAMP GUIDE

LED MR-16 Lamps



SLMR166XXW27
SLMR166XW27
SLMR166W27
SLMR166M27
SLMR166N27

Beam	Beam Angle	Halogen Equiv.	Lamp Body Color	Level 5, 6W	Voltage Input	CCT	Watts	Amps	Power Factor	Volt Amp	Bare Lamp Lumens	Light Output	CRI
XX-Wide	80°	75 Watt	White	Level 5, 6W	10-24 VAC	2700°K	5.92	0.697	0.714	8.29	720	213	83
X-Wide	55°						5.98	0.695	0.715	8.36		440	
Wide	40°						6.09	0.706	0.717	8.49		527	
Medium	30°						5.94	0.687	0.718	8.27		575	
Narrow	20°						6.07	0.697	0.727	8.35		559	



SLMR165XXW27
SLMR165XW27
SLMR165W27
SLMR165M27
SLMR165N27

Beam	Beam Angle	Halogen Equiv.	Lamp Body Color	Level 4, 5W	Voltage Input	CCT	Watts	Amps	Power Factor	Volt Amp	Bare Lamp Lumens	Light Output	CRI
XX-Wide	80°	50 Watt	Black	Level 4, 5W	10-24 VAC	2700°K	4.71	0.544	0.716	6.58	540	175	83
X-Wide	55°						4.62	0.543	0.702	6.58		392	
Wide	40°						4.59	0.542	0.7	6.56		419	
Medium	30°						4.7	0.551	0.703	6.69		421	
Narrow	20°						4.515	0.531	0.704	6.41		381	



SLMR164XXW27
SLMR164XW27
SLMR164W27
SLMR164M27
SLMR164N27

Beam	Beam Angle	Halogen Equiv.	Lamp Body Color	Level 3, 4W	Voltage Input	CCT	Watts	Amps	Power Factor	Volt Amp	Bare Lamp Lumens	Light Output	CRI
XX-Wide	80°	35 Watt	Blue	Level 3, 4W	10-24 VAC	2700°K	3.277	0.393	0.691	4.74	390	199	84
X-Wide	55°						3.135	0.378	0.69	4.54		299	
Wide	40°						3.224	0.387	0.691	4.67		304	
Medium	30°						3.136	0.375	0.693	4.53		305	
Narrow	20°						3.236	0.387	0.692	4.68		267	



SLMR162XXW27
SLMR162XW27
SLMR162W27
SLMR162M27
SLMR162N27

Beam	Beam Angle	Halogen Equiv.	Lamp Body Color	Level 2, 2W	Voltage Input	CCT	Watts	Amps	Power Factor	Volt Amp	Bare Lamp Lumens	Light Output	CRI
XX-Wide	80°	20 Watt	Green	Level 2, 2W	10-24 VAC	2700°K	1.868	0.228	0.671	2.78	300	128	84
X-Wide	55°						1.814	0.226	0.663	2.74		183	
Wide	40°						1.88	0.236	0.664	2.83		189	
Medium	30°						1.84	0.233	0.66	2.79		193	
Narrow	20°						1.85	0.23	0.663	2.79		167	



SLMR161XXW27
SLMR161XW27
SLMR161W27

Beam	Beam Angle	Halogen Equiv.	Lamp Body Color	Level 1, 1W	Voltage Input	CCT	Watts	Amps	Power Factor	Volt Amp	Bare Lamp Lumens	Light Output	CRI
XX-Wide	80°	10 Watt	Red	Level 1, 1W	10-24 VAC	2700°K	1.058	0.139	0.63	1.68	240	74	84
X-Wide	55°						1.065	0.139	0.63	1.69		106	
Wide	40°						1.075	0.143	0.636	1.69		104	