




LAMP GUIDE

Mini LED Lamps



SLBP250L

Description:

- GY6.35 Bi-Pin Base LED
- 2.5 Watts, 9 - 20 Volt operating range
 - 250 Lumen, Color Temp. 2750°K
 - IP67 Rated, 25,000 Hrs.

Can be used with these Products:



Source Path/ Area Lights
(SAL100, SAL150, SALSTEM12, SALSTEM18)
*all pieces sold separately



CAST LANDSCAPE
Classic Mini China Hat
CCH5CB (with Bi-Pin Socket)
CCH5LED1 (original non-integrated)



SLSCB250L

Description:

- Single Contact Bayonet LED
- 2.5 Watts, 9 - 20 Volt operating range
 - 250 Lumen, Color Temp. 2750°K
 - IP67 Rated, 25,000 Hrs.

Can be used with these Products:

CAST LANDSCAPE



Classic Mini China Hat
CCH5CB (with SCB Socket)
CCH5LED1 (original non-integrated)

Classic Path Lights, Niche Light, & Deck Light
CCH***, CMU***, CNO***, CNL1CB, & CDL1CB
Manufactured Before July 2007



SL3156250L

Description:


- 3156 S8 Wedge Base LED
- 2.5 Watts, 9 - 20 Volt operating range
 - 250 Lumen, Color Temp. 2750°K
 - IP67 Rated, 25,000 Hrs.

Can be used with these Products:

CAST LANDSCAPE



Classic Path Lights
CCH13CB, CCH1CB, CCH2CB, CMU13CB, CMU1CB, CMU2CB, CNO13CB, CNO1CB, CSA1CB
Manufactured After July 2007




SL921T5200L

Description:

- 921 T5 Wedge Base LED
- 2.5 Watts, 9 - 15 Volt operating range
 - 200 Lumen, Color Temp. 2750°K
 - IP67 Rated, 25,000 Hrs.

Can be used with these Products:

CAST LANDSCAPE



Classic Deck, Niche, & Engineered Wall Lights
CDL1CB, CDL2CB, CNL1CB, CEWL5CB, & CEWL6CB



LED MR-16 LAMP GUIDE

NEW 3000K Color Temp Lamps

 Lamp Code	Beam from Fixture		Halogen Equiv.	Lamp Body Color Code	Voltage Input	Color Temp. CCT/CRI	Amps	Power Factor	Volt Amp (to size)	Factory Lumen	Lumen Output Enclosed Fixture	Rated Hrs.
SLMR166XXW27	XX-Wide	80°	75 Watt	WHITE 6 Watt	10-24 VAC	2700°K/ 83 CRI	0.706	0.717	8.49	720	213	50,000
SLMR166XW27	X-Wide	55°					0.706	0.717	8.49		440	
SLMR166W27	Wide	40°					0.706	0.717	8.49		527	
SLMR166M27	Medium	30°					0.706	0.717	8.49		575	
SLMR166N27	Narrow	20°					0.706	0.717	8.49		559	
SLMR166XW30	X-Wide	55°				3000°K/ 83 CRI	0.762	0.681	9.16		534	
SLMR166W30	Wide	40°					0.745	0.677	9.0		557	
 Lamp Code	Beam from Fixture					Halogen Equiv.	Lamp Body Color Code	Voltage Input	Color Temp. CCT/CRI		Amps	
SLMR165XXW27	XX-Wide	80°	50 Watt	BLACK 5 Watt	10-24 VAC	2700°K/ 83 CRI	0.542	0.7	6.56	540	175	50,000
SLMR165XW27	X-Wide	55°					0.542	0.7	6.56		392	
SLMR165W27	Wide	40°					0.542	0.7	6.56		419	
SLMR165M27	Medium	30°					0.542	0.7	6.56		421	
SLMR165N27	Narrow	20°					0.542	0.7	6.56		381	
SLMR165XW30	X-Wide	55°				3000°K/ 83 CRI	0.671	0.658	7.45		426	
SLMR165W30	Wide	40°					0.608	0.658	7.34		456	
 Lamp Code	Beam from Fixture					Halogen Equiv.	Lamp Body Color Code	Voltage Input	Color Temp. CCT/CRI		Amps	
SLMR164XXW27	XX-Wide	80°	35 Watt	BLUE 4 Watt	10-24 VAC	2700°K/ 83 CRI	0.387	0.691	4.67	390	199	50,000
SLMR164XW27	X-Wide	55°					0.387	0.691	4.67		299	
SLMR164W27	Wide	40°					0.387	0.691	4.67		304	
SLMR164M27	Medium	30°					0.387	0.691	4.67		305	
SLMR164N27	Narrow	20°					0.387	0.691	4.67		267	
SLMR164XW30	X-Wide	55°				3000°K/ 83 CRI	0.435	0.637	6.0		310	
SLMR164W30	Wide	40°					0.435	0.65	5.26		322	
 Lamp Code	Beam from Fixture					Halogen Equiv.	Lamp Body Color Code	Voltage Input	Color Temp. CCT/CRI		Amps	
SLMR162XXW27	XX-Wide	80°	20 Watt	GREEN 2 Watt	10-24 VAC	2700°K/ 83 CRI	0.236	0.664	2.83	300	128	50,000
SLMR162XW27	X-Wide	55°					0.236	0.664	2.83		183	
SLMR162W27	Wide	40°					0.236	0.664	2.83		189	
SLMR162M27	Medium	30°					0.236	0.664	2.83		193	
SLMR162N27	Narrow	20°					0.236	0.664	2.83		167	
SLMR162XW30	X-Wide	55°				3000°K/ 83 CRI	0.249	0.64	3.0		197	
SLMR162W30	Wide	40°					0.23	0.66	3.0		196	
 Lamp Code	Beam from Fixture					Halogen Equiv.	Lamp Body Color Code	Voltage Input	Color Temp. CCT/CRI		Amps	
SLMR161XXW27	XX-Wide	80°	10 Watt	RED 1 Watt	10-24 VAC	2700°K/ 83 CRI	0.139	0.63	1.69	240	74	50,000
SLMR161XW27	X-Wide	55°					0.139	0.63	1.69		106	
SLMR161W27	Wide	40°					0.139	0.63	1.69		104	