Lighting Specification Sheet

Classic Mini China Hat Area/Path Light (CCH5CB, CCH5LED1)



Old world craftsmanship...tomorrow's technology®

Project:	Date:
Fixture Type:	
Specifier:	
Drawing not to scale	Optimal voltage is 9-20 volts. Check voltage with digital multimeter.
Highly reflective white underside surface paint.	Extremely durable solid sand-cast bronze body and cap.
Reflected no-glare light source.	Thick-walled borosilicate glass lamp enclosure.
2.5W Bi-Pin LED Lamp (included).	High temperature corrosion-resis- tant socket.
	Soldered, crimped and heat shrunk electrical connection to lead wire.
	Heavy duty 100% copper fixture stem.
Install 90º to grade.	Quick release feature allows stem insertion after setting stake in ground.
Set stake top flush with ground.	
Pre-wired with 25 ft. #16/2 tin-coated, marrine-grade No-0x wire.	Extremely durable solid Brass stake Soil
Bury at 6" depth.	Compact backfill in 4" lifts.
Coil leftover lead wire at base of fixture. This allows for future field adjustment of fixture placement if required.	
• CCH5CB:Requires 2.5 W Bi-Pin LED Lamp (included).	Plan Symbol:
• CCH5LED1: 10-24 VA/DC Integrated LED (incl.)	OUNTING OPTIONS

★ Small Mounting Stake (CMS5CB)(incl.)□ MR-11 Mounting Canopy (XCBPTMC2)