



SIDE VIEW WITH ROTATION



SIDE VIEW



FEATURES:

- -Solid Copper and Brass Construction
- -Solid Copper 45 Degree Shroud for Glare Minimization
- -High Heat Silicone O-Rings
- -Beryllium Socket with 3ft 18/2 Power Lead

FINISHES:

- -Natural Copper
- -Antique
- -Dark Antique
- -Black
- -Verde
- -Rust

LAMPS:

- -12 Volt MR-16 in 10, 20, 35 & 50 Watts with a 12, 24, 36 & 60 Degree Spread (EXCEPTION: 10 watt only available in 32 degree spread)
- -LED MR-16's
- -50 Watt Maximum

LENS:

-3mm CLEAR FORGED BOROSILICATE GLASS

MOUNTING:

- -Black ABS Ground Stake 8 ½" Long with Female 1/2" NPT (STANDARD)
- -Brass Threaded (Female $\frac{1}{2}$ " NPT) or Non-Threaded Ground Stake 9 1/2 " Long
- -Brass Threaded (Female ½" NPT) or Non-Threaded Flush Mount (Deep or Shallow Housing)
- -Aluminum Tree Mount (Female ½" NPT) with Brown Powder Coat Finish
- -Copper Stem Risers-1" Diameter (Female ½" NPT) or ¾' Diameter (Female ½" NPT)
 - -Available in custom heights

ACCESSORIES:

- -MR-16 Honeycomb Louver
- -MR-16 Lamp Clip
- -MR-16 Clear Spread Lens
- -MR-16 Prismatic Lens
- -MR-16 Colored Lens (Ice Blue, Lavender, Amber, MV Green, Red & Rose)
- -25ft. & 50 ft. 16/2 Leads Available



