



📰 🔝 I



CONTINUA

Seam·less ('semles)

Smooth. Continuous. Light. A linear lighting system in its purest form.

Meet Corelite Continua:

The definition of seamless, in lighting design.

Watch creativity unravel

Say goodbye to lens gaps and breaks in illumination common in traditional linear runs. With Continua, seamless illumination is possible with a proprietary flexible continuous roll lens that won't ripple or bow over long lengths. The result is high quality uniform illumination along the entire run length for a truly unique aesthetic.

Corelite


Corridor CTA-F-7525-20L830 75% Up / 25% Down 2000Ims (500 Ims per ft) Power Density: 0.3 W / Ft²


Go further with excellent optical control

The Continua features precision engineered optical control to create optimal light distributions.

Uplight – wide smooth batwing distribution enables broader row spacing with the potential to use less fixtures while achieving the target illumination.

Downlight – optically optimized to reduce overall fixture height while creating soft uniform illumination on the diffuse lens below.





Choose from a full range of direct/indirect distributions or specify a custom distribution.

| 75%↑ | 25%↓ |
|-------------|-------|
| 50%↑ | 50%↓ |
| 25%↑ | 75%↓ |
| 0%↑ | 100%↓ |
| Specify ↑↓ | |



Corelite

Classroom CTA-F-7525-40L835-2D 75% Up / 25% Down 4000lms (1000 lms per ft) Power Density: 0.4 W / Ft²

Workspace CTA-F-5050-30L835 50% Up / 50% Down 3000Ims (750 Ims per ft) Power Density: 0.4 W / Ft²

TU

Small scale, big impact


Continua's unique design puts the focus on the continuous seamless line of light. Measuring only 2.4" tall by 7" wide, the luminous surface area is maximized on the bottom aperture for a clean aesthetic with minimal lines. Despite its compact size, the Continua utilizes integral LED drivers, emergency battery packs, and sensors to make it easier to specify and install.

in the log of the

Installation versatility

Installation time is minimized with the use of Corelite's modular section design, through wiring, and simple joining features.

- 4', 8', 12' simple building blocks to create longer runs.
- Complex wiring is achievable while keeping power feeds to a minimum.
- Joining fixtures is quick and provides a ridged and tight connection.
- Navigate existing ceiling obstructions with variable mounting locations.
- Integral drivers and continuous through wiring allows for a single power feed connection up to 150ft (277V).
- The 12 ft. unit advantage Reduce time and labor costs during installation with 33% fewer fixtures, joint connections, and mounting points compared to 8 ft. unit max.




Connected lighting enabled solution

Corelite Continua LED luminaires are designed to support integrated sensors, providing code compliance, installation and energy savings while unlocking the potential of connected lighting systems. The Continua's unique sensor integration simplifies the control design without impacting the seamless illumination aesthetic. With sensors factory-installed in every fixture, the fixture layout enables optimal sensor coverage and controllability. Continua deploys Cooper Lighting Solutions' integrated connected lighting system options, making your facility smarter so you can make smarter decisions.



- Wireless Connected Lighting System Easy to use mobile application allows for fast set up and unlocks advanced control capabilities



SERIES CTA, Contin SHIELDING

Continuous

DISTRIBUT

75% Up/25 50% Up/50 Specify XX L

LUMEN PA

2000 Lms (5 3000 Lms (7 4000 Lms (1

COLOR TEM

LED 3000K LED 3500K LED 4000K

VOLTAGE

347 VAC

FINISH

White Silver Black

RUN LENGTH

11 12' Continuous (up to 100')**

OPTIONS

Independent Up/Down Circuits Emergency Circuit Integral Battery Pack Integral WaveLinx Sensor or LumaWatt Pro Sensor

ADDITIONAL INFORMATION: Warranty: 5 year cULus: Damp Location Listed LM79/LM80: Compliant RoHS: Compliant

L85 @ 60.000 hours



Corelite


Technical specifications


| nua Direct/Indirect Suspended | | |
|-------------------------------|------------------------|--|
| 3 | | |
| Roll Lens | | |
| ION | | |
| 5% Down | 25% Up/75% Down | |
| 0% Down | 0% Up / 100% Down | |
| Up/ XX Down† | | |
| CKAGE | | |
| 500 lms/ft) | 5000 Lms (1250 lms/ft) | |
| 750 lms/ft) | 6000 Lms (1500 lms/ft) | |
| 1000 lms/ft) | | |
| MPERATURE | | |
| | | |


Universal 120V-277 VAC

Custom color









[†] Not all distributions available. Consult factory for more details.

*Specifications and dimensions subject to change without notice. Please refer to product specification sheet for the most updated technical data

**Consult factory for runs bigger than 100'.

Lighting Product Lines

Ametrix AtLite Corelite Ephesus Fail-Safe Halo Halo Commercial Invue io Iris Lumark Lumière McGraw-Edison Metalux MWS Neo-Ray Portfolio RSA Shaper Streetworks Sure-Lites

Controls Product Lines

Fifth Light Technology Greengate iLight (International Only) iLumin Zero 88

Connected Lighting Systems

Distributed Low-Voltage Power HALO Home iLumin Plus Enlighted WaveLinx Trellix

Cooper Lighting Solutions 18001 East Colfax Avenue

Aurora, CO 80011 P: 303-393-1522 www.cooperlighting.com

COOPER Lighting Solutions Canada Sales 5925 McLaughlin Road Mississauga, Ontario L5R 1B8 P: 905-501-3000 F: 905-501-3172 © 2021 Cooper Lighting Solutions All Rights Reserved Printed in USA Publication No. BR525096EN May 26, 2021 9:40 AM Cooper Lighting Solutions is a registered trademark.

All other trademarks are property of their respective owners.

Product availability, specifications, and compliances are subject to change without notice.