



landscape • entertainment • architectural • hospitality • illumination

DL-42/43/45 SERIES DIRECTIONAL LIGHT



DL-43-LEDM11-BAR w/ FA-24MD-BAR



DL-42-LEDM7-BRS



DL-43-LEDM11-BAR



DL-45-LEDM7-BAR



DIRECTIONAL LIGHTS

DL-43-LEDM11



TYPE

SPECIFICATIONS

CONSTRUCTION: Cast aluminum or Cast brass integrated heat sink base; matching cast adjustable swivel with 240° rotation; Extruded aluminum, brass or copper housing (copper housing has brass base)

LENS: High impact clear tempered convex glass

O-RING: 2x High temperature red silicone

LIGHT SOURCE: Integrated 590 lumen 11w LED module (equivalent to 50w halogen) with 6 high power Cree XP-G LEDs; 50,000 hours average rating. 2800k color temperature.

OPTICS: Interchangeable spot (15°), flood (40°), wide flood (60°) and 160° very wide flood (no optics)

12v DRIVER: Integrated on-board, no external driver required. 12v AC/DC input. Voltage range 9-18v; Optimum operating range 12v-15v

120v DRIVER: HW-1212LED* 120v Input, 12v AC output LED Driver

120v/277v DRIVER: HW-12-20MVLED* 90v-277v Input, 12v DC output LED Driver

*Must use FA-26 mounting post or junction box

WIRING: Black 3 foot 18/2 zip cord from base of fixture (12v only)

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable (12/2, 10/2 or 8/2 only)

MOUNTING:

Aluminum model: FA-03 black 9" ABS stake, tapped 1/2" NPS

Brass & Copper models: FA-03-LG large black 9" ABS stake, tapped 1/2" NPS

FINISH: Aluminum - Black texture polyester powder coat. Optional finishes available.


Brass & Copper - Unfinished. Optional finishes available.



DL-43-LEDM1140-BLT

ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
DL-43-LEDM1115-BLT	Aluminum Bullet, 15° Optics	11w LED Module	3.0 lbs.
DL-43-LEDM1140-BLT	Aluminum Bullet, 40° Optics	11w LED Module	3.0 lbs.
DL-43-LEDM1160-BLT	Aluminum Bullet, 60° Optics	11w LED Module	3.0 lbs.
DL-43-LEDM11WF-BLT	Aluminum Bullet, No Optics	11w LED Module	3.0 lbs.
DL-43-LEDM1115-BRS	Brass Bullet, 15° Optics	11w LED Module	5.0 lbs.
DL-43-LEDM1140-BRS	Brass Bullet, 40° Optics	11w LED Module	5.0 lbs.
DL-43-LEDM1160-BRS	Brass Bullet, 60° Optics	11w LED Module	5.0 lbs.
DL-43-LEDM11WF-BRS	Brass Bullet, No Optics	11w LED Module	5.0 lbs.
DL-43-LEDM1115-COP	Copper Bullet, 15° Optics	11w LED Module	5.0 lbs.
DL-43-LEDM1140-COP	Copper Bullet, 40° Optics	11w LED Module	5.0 lbs.
DL-43-LEDM1160-COP	Copper Bullet, 60° Optics	11w LED Module	5.0 lbs.
DL-43-LEDM11WF-COP	Copper Bullet, No Optics	11w LED Module	5.0 lbs.



Beam Type	Angle	Visual Indicator
Spot	15°	Red Dot
Flood	40°	Green Dot
Wide Flood	60°	Blue Dot



BEAM/GLARE CONTROL ACCESSORIES

FA-08-DL-42-21	Round 1/4" Hex Cell Louver
FA-35-DL-42-GREEN	Green Acrylic Insert Lens
FA-11-DL-42-BLUE	Blue Tempered Glass Insert Lens
FA-11-DL-42-GREEN	Light Green Tempered Glass Insert Lens
FA-11-DL-42-AMBER	Amber Tempered Glass Insert Lens
FA-11-DL-42-RED	Red Tempered Glass Insert Lens
FA-104-DL-42-SB	Wide Spread Sandblasted Glass Insert Lens Softener



JOB INFORMATION

Type: _____ Date: _____

Job Name: _____

Cat. No.: _____

Lamp(s): _____

Specifier: _____

Contractor: _____

Notes: _____

FOCUS INDUSTRIES INC.® www.focusindustries.com
 25301 COMMERCENTRE DRIVE sales@focusindustries.com
 LAKE FOREST, CA 92630 (949) 830-1350 • FAX (949) 830-3390

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT



DIRECTIONAL LIGHTS

DL-43-LEDM11

TYPE

MOUNTING ACCESSORIES

FA-03-BRS: 9.00" 229mm, 2" 51mm

FA-03-LG: 9.00" 229mm, 3" 76mm

FA-03-RX-BRS: 7.00" 178mm, 2" 51mm

FA-24-BRS: 0.9" 23mm, 3" 76mm

FA-22-CST-BRS: 5.75" 146mm, 3.50" 89mm, 1.125" 29mm

FA-24MD-CST-T-BRS (10"-41")

FA-24-MD-CST-BRS: 2.65" 67mm, 1.4" 36mm

FA-24-MD-CST-PC-BRS: 2.65" 67mm, 1.4" 36mm

FA-22-T-BRS (10"-41")

FA-24-LG-CST-BRS: 4.75" 121mm

FA-24-LG-SPUN-COP: 0.875" 22mm

FA-111-T-BRS (10"-41")

FA-111-BRS: 2.65" 67mm, 1.4" 36mm

C/FA-111-BRS

FA-30-4-PVC-BRS: 4" 102mm

FA-30-8-PVC-BRS: 8" 203mm

FA-01-BRS: 15" 381mm, 1.63" 41mm


FA-24-MD-CST-POST-BRS: 13" 330mm

FA-24-MD-CST-POST2-BRS (telescopic): 16" 406mm, Telescopic to 26"


C/FA-25/-26/-BRS: 20" 508mm, 3" 76mm

STEM EXTENSIONS: FA-30 (10" 254mm), FA-31 (13" 330mm), FA-32 (16" 406mm), FA-33 (21" 533mm), FA-34 (26" 660mm)


LIGHT DISTRIBUTIONS AND PHOTOMETRICS



DL-43-LEDM1115
15° SPOT



DL-43-LEDM1140
40° FLOOD



DL-43-LEDM1160
60° WIDE FLOOD