

THE EOS 1.0
HIGHLIGHTS

EOS 1.0

FORM & FUNCTION



Introducing the sleekest luminaire from our EOS family. The EOS 1.0 features a sleek and minimal profile with an aperture of just 1.68-inches, which still enables the 1.0 to have an integral driver.

Designed for beauty and built for performance, the EOS series of luminaires can be customized to fit your lighting needs with optional color temperature, drivers, sensors and more.

LUMINAIRE SPECIFICATIONS

Efficacy : up to 102 lm/W

Lumen Package: 375-1000 lm/ft

Distribution: Pendant Direct, Pendant Direct/
Indirect

Configurations: 4ft - 8ft Individual Units or
Continuous Runs.

Fixed CCT: 27K, 30K, 35K, 40K


Tunable White: 2700K - 6500K



Pendant Direct



Pendant Direct/Indirect



EOS 1.0 OPTIONS



TUNABLE WHITE SOLUTIONS

Lux Illuminaire utilizes the latest sensors and controls to provide you with the options you're looking for in your lighting fixtures.

Standard 0-10v - 2 Channel Control (Optional Dim to Warm and Optional Blue Tooth Enabled)

Lutron T-Series 2-Channel Driver pairs with Lutron's Quantum System

OSRAM Tunable White Standalone Solution with OSRAM Wall Station

OSRAM 2-Channel Tunable White LED Driver, Dexam Driver with Optional DALI mode (58287)

DRIVER SPECIFICATIONS

All of our luminaires come standard with 1% dimming and THD <20% utilizing 0-10v constant current protocol. 120v/277v is standard with the option of 347v.

EOS 1.0 COMING SOON

The EOS 1.0 family will expand it's product offering to include the following distributions.

Recessed

Wall Direct

Wall Direct/Indirect

Surface

FINISH OPTIONS

Polyester powder, low gloss, textured paint finish applied after a multi-stage pretreatment. Standard luminaire finishes include white, silver, and black. Custom color options are available. (Consult Factory).

STANDARD FINISHES



BLACK



WHITE



SILVER



LU  ILLUMINAIRE