

THE EOS 4.0
HIGHLIGHTS

EOS 4.0

FORM & FUNCTION



Introducing the most robust luminaire to date to join our EOS family, the EOS 4.0. The EOS 4.0 has an aperture of 4-inches making it the largest luminaire in the EOS line. The 4.0 delivers a minimalist profile that was designed for beauty and built for performance, staying true to the integrity and efficacy you have come to expect from LUX. Pairing innovative features with the ability to customize optional color temperature, drivers, sensors and more, LUX empowers you to choose the perfect luminaire to fit your needs.

LUMINAIRE SPECIFICATIONS

Efficacy : up to 126 lm/W

Lumen Package: 375-1250 lm/ft

1% 0-10%v Dimming Standards

L80 calculated at 80,000 hours

Available in 4" Aperture

Configurations: 2ft - 8ft Individual Units or

Continuous Runs.

Fixed CCT: 27K, 30K, 35K, 40K

Tunable White: 2700K - 6500K

CRI: +84 an +92



Pendant Direct



Pendant Direct/Indirect




Recessed



Wall Direct




Wall Indirect



Wall Direct/Indirect



Surface



EOS 4.0 OPTIONS



TUNABLE WHITE SOLUTIONS

Lux Illuminaire utilizes the latest sensors and controls to provide you with the options you're looking for in your lighting fixtures.

Standard 0-10v - 2 Channel Control (Optional Dim to Warm and Optional Blue Tooth Enabled)

Lutron T-Series 2-Channel Driver pairs with Lutron's Quantum System

OSRAM Tunable White Standalone Solution with OSRAM Wall Station

OSRAM 2-Channel Tunable White LED Driver, Dexam Driver with Optional DALI mode (58287)

DRIVER SPECIFICATIONS

All of our luminaires come standard with 1% dimming and THD <20% utilizing 0-10v constant current protocol. 120v/277v is standard with the option of 347v.

EOS 4.0 COMING SOON

The EOS 4.0 family will expand it's product offering to include the following distributions.

Asymmetric Wall Wash

Wall Graze


Perimeter

Indirect Extreme Bat Wing

FINISH OPTIONS

Polyester powder, low gloss, textured paint finish applied after a multi-stage pretreatment. Standard luminaire finishes include white, silver, and black. Custom color options are available. (Consult Factory).

STANDARD FINISHES



LU  ILLUMINAIRE