

| | | | | | |
|-------------|--|-----------|--|------|--|
| Project | | Catalog # | | Type | |
| Prepared by | | Notes | | Date | |



Fail-Safe

FC22 Sealed Cruze ST 2x4

2x4 Sealed Center Basket
Sterile Environments / Behavioral Health
Curved or Square Lens
3,000 to 17,000 lumens

Typical Applications

Medical • Cleanroom • Behavior Health • Education • Laboratory • Pharmacy • Fitness Center • R&D Center

Interactive Menu

- Order Information [page 2](#)
- Photometric Data [page 3](#)
- VividTune Tunable White [page 5](#)
- Product Warranty

Product Certification




Product Features




Top Product Features

- Sealed center basket luminaire for use in high abuse, medical, wet location, and sterile applications
- Wet location standard, IP65 standard for dust and water ingress protection
- NSF listed for use in food services/food preparation environments
- Clear polycarbonate bottom lens for use in **behavioral health applications**
- ISO5-9 certified
- VividTune tunable white (3000K-5000K and 2700K-6500K) available in 80CRI or 90CRI
- Options to meet Buy American and other domestic preference requirements
- IK10 with Polycarbonate Lens

Dimensional and Mounting Details (standard curved lens shown)




Ceiling Compatibility



| Ceiling Type | Trim Type |
|--------------|-----------|
| Exposed Grid | Standard |
| Concealed T | Standard |
| Slot Grid | Standard |
| Flange | * |

*See Drywall Frame Kit Accessory in Ordering Information Section

Optional Square Lens



Order Information

SAMPLE ORDER NUMBER: **24FCZ2-40HE-UNV-L840-CP125-CD1**

| Domestic Preferences | Series | Lumen Output | | Shielding | Voltage | Options CRI/CCT | Flex | |
|--|---|--|--|---|--|--|--|---|
| Domestic Preferences ⁽¹⁶⁾ | Series | Lumen Level | Efficacy | Shielding | Voltage ⁽²⁾ | CRI/CCT | Flex | |
| [Blank] =Standard BAA =Buy American Act TAA =Trade Agreements Act | 24FCZ2 =24 inch width, 4 ft. length | 30 =3000 Lumens 35 =3500 Lumens 40 =4000 Lumens 45 =4500 Lumens 50 =5000 Lumens 55 =5500 Lumens ⁽¹⁰⁾ 60 =6000 Lumens ⁽¹⁰⁾ 65 =6500 Lumens ^{(10), (12)} 70 =7000 Lumens 75 =7500 Lumens ^{(11), (12)} | 80 =8000 Lumens ⁽¹¹⁾ 85 =8500 Lumens ⁽¹¹⁾ 90 =9000 Lumens ⁽¹¹⁾ 95 =9500 Lumens ⁽¹¹⁾ 100 =10000 Lumens ⁽¹¹⁾ 110 =11000 Lumens ⁽¹¹⁾ 120 =12000 Lumens ⁽¹¹⁾ 130 =13000 Lumens ⁽¹¹⁾ 150 =15000 Lumens ⁽¹¹⁾ 170 =17000 Lumens ⁽¹¹⁾ | [Blank] =Standard Efficacy ⁽¹³⁾ HE =High Efficacy ⁽¹⁴⁾ VHE =Very High Efficacy ^{(11), (15)} | [Blank] =Ribbed Frosted Acrylic Curved Lens (standard) S =Smooth Frosted Acrylic Curved Lens RDP =Smooth Curved Lens with Round Pattern Insert HRP =Curved Lens High-Efficiency Round Perf Inlay SQR =Square Lens | UNV =Universal Voltage 120-277 347V =347 Volt ⁽⁵⁾ | L830 =80CRI, 3000K L835 =80CRI, 3500K L840 =80CRI, 4000K L850 =80CRI, 5000K L83050 =80CRI 3000K-5000K White Tuning ⁽⁷⁾ L82765 =80CRI 2700K-6500K White Tuning ⁽⁷⁾ L930 =90CRI, 3000K L935 =90CRI, 3500K L940 =90CRI, 4000K L950 =90CRI, 5000K L93050 =90CRI 3000K-5000K White Tuning ⁽⁷⁾ L92765 =90CRI 2700K-6500K White Tuning ⁽⁷⁾ | [Blank] =No Flex A3/8-4/18GDIM =3/8" Flex with 0-10V Dimming Leads A3/8-2/18G =3/8" Flex with line and common A3/8-5/18GDIM =Flex with 0-10V Dimming leads and Blue for alternate wiring. See below for details. |
| Notes (16) Only product configurations with these designated prefixes are built to be compliant with the Buy American Act of 1933 (BAA) or Trade Agreements Act of 1979 (TAA), respectively. Please refer to DOMESTIC PREFERENCES website for more information. Components shipped separately may be separately analyzed under domestic preference requirements. | Notes (10) Not available with white tuning and Standard Efficacy. (11) Currently only available with CD driver option. (12) 6500 lumens standard efficacy and 7500 lumens and higher are not available with WN driver. (13) Available up to 6500 lumens. (14) Available up to 7500 lumens. (15) Requires 2 CD-1 drivers above 100VHE. | Notes (2) Products also available in non-US voltages and frequencies for international markets. (5) 347 versions 6000 lumens and below are available with emergency options, 347 versions with emergency 5LTHD, step-dim or sensors are not available. | Notes (7) White tuning provides correlated color temperatures (CCT) between 3000K (warm) to 5000K (cool) or 2700K (warm) to 6500K (cool). Must be used in conjunction with W2A driver only. Must be used with two (2) 10V dimming control channels, 1 color, 1 intensity. Not compatible with other control or sensor options. | Notes (9) Two drivers are required for the following packages: 65 347V CD, 75HE 347V CD. When combined with emergency total height is increased by 1 inch. | Notes (9) Two drivers are required for the following packages: 65 347V CD, 75HE 347V CD. When combined with emergency total height is increased by 1 inch. | Flexible Metal Conduit Options Flex options available for 0-10V dimming control, DALI dimming control, emergency and night light functions. 72-inch factory-installed and pre-wired to driver, fitted to luminaire housing access plate with 90° enclosed FMC connector. Not all options may be combined and installation ratings vary by type. A3/8-4/18GDIM series notes: Factory installed dimming option 3/8" flexible metal conduit with 2-#18 power and ground wires and 2-#18 UL-listed jacketed 0-10V +/- control wires. Meets UL 66, 83, 1479, 1569, 1581, 2556. NEC® 250.118, 300.22(C), 392, 396, 330, 501, 502, 503, 530, 504, 505, 518, 520, 530, 645, 72; Federal Specification A-A-59544 (formerly J-C-30B); all applicable OSHA and HUD Requirements. UL Classified 1-, 2-, and 3-hour through penetration with applicable fire stop product (not included). May be surface mounted, fished and/or embedded in plaster. Cable tray and approved raceway rated, install per NEC®; Environmental Air-Handling Space Installation per NEC® 300.22(C). | | |

| Bottom Lens | Driver Type | Number of Drivers | Options |
|---|---|---|---|
| CA08 =0.080" Clear Acrylic CA125 =0.125" Clear Acrylic CP125 =Clear Polycarbonate 0.125" CP187 =Clear Polycarbonate 0.187" CP250 =Clear Polycarbonate 0.250" | CD =0-10V Driver (10%-100% Dimming) HCD =0-10V Driver (1%-100% Dimming) 5LTD =DALI Driver (5%-100% Dimming) 5LTHD =DALI Driver (1%-100% Dimming) SD =Step Dimming Driver (50% or 100% Dimming) LH =Lutron HiLume (LDE1 series) 1%-100% EcoSystem Driver with Soft-on Fade to Black dimming ^(F) W2A =White Tuning, 2 ch, Analog 0-10V Intensity and CCT Control ⁽⁷⁾ | 1 =1 Driver 2 =2 Drivers ⁽⁹⁾ | [Blank] =No Element Fuse GL =Single Element Fuse GM =Double Element Fuse AMW =Anti-microbial, Powder Coat, Matte White Paint |
| Notes (7) White tuning provides correlated color temperatures (CCT) between 3000K (warm) to 5000K (cool) or 2700K (warm) to 6500K (cool). Must be used in conjunction with W2A driver only. Must be used with two (2) 10V dimming control channels, 1 color, 1 intensity. Not compatible with other control or sensor options. Integrated options must be used in conjunction with the associated system and may not be compatible with other options or accessories. Please refer to the following: (F) Consult Marketplace Options - Lutron system pages for additional details and compatibility. Compatible only with driver series shown, and may require two or more drivers. Requires field commissioning to operate or dim. Contact Lutron at www.lutron.com | Notes (9) Two drivers are required for the following packages: 65 347V CD, 75HE 347V CD. When combined with emergency total height is increased by 1 inch. | Notes (9) Two drivers are required for the following packages: 65 347V CD, 75HE 347V CD. When combined with emergency total height is increased by 1 inch. | Notes (9) Two drivers are required for the following packages: 65 347V CD, 75HE 347V CD. When combined with emergency total height is increased by 1 inch. |

| Emergency | Integrated Sensing Systems | Accessories |
|--|--|--|
| Options Emergency [Blank] =No Emergency Pack EL7W =7-watt, 120V-277V emergency battery pack installed ⁽³⁾ EL14W =14-watt 120V-277V emergency battery pack installed ⁽³⁾ GTR2 =Generator Transfer Relay ⁽⁶⁾ ETRD =Emergency Transfer Relay with dimming control ⁽⁶⁾ | Integrated Sensing Systems [Blank] =No Sensor LWTPD1 =Enlighted Wireless Tile-mount Sensor ⁽⁸⁾ | Accessories (order separately) ⁽¹⁷⁾ [Blank] =No Accessory FCZ2-EQCLIP-U-PK =Pack of four Fail-Safe Cruze grid security clips ⁽¹⁾ DFCL-2448W-U =2' x 4' gasketed drywall framing kit. Ships with gasket to be applied in field. Cutout Dimensions 24.25" x 48.25" ⁽¹⁸⁾ DFVR/FCZ-2448W-U =2' x 4' secured tamper resistant drywall kit. Cutout dimensions 24.25" x 48.25" ⁽¹⁸⁾ ISHH-01 =Programming Remote for Integrated Sensor ⁽⁹⁾ ISHH-02 =Personal Control Remote for Integrated Sensor ⁽⁹⁾ |
| Notes (3) With integral test switch/indicator/laser test. For approximate delivered lumens multiply the lumens per watt of the desired fixture by the wattage of the emergency battery pack (100 lm/W x 7=700 lumens). IES-format photometry for luminaire under emergency operation available. (6) Used to bypass local control during outage. Must be used in conjunction with UL 1008 device (provided by others). GTR2 option includes 2 relays on fixtures with dimming drivers. ETRD option only requires one relay when used on a dimming fixture. Must specify voltage as 120V or 277V when ordering these devices. 347 not available. Integrated options must be used in conjunction with the associated system and may not be compatible with other options or accessories. | Integrated Sensing and Control System Options NOTES: Integrated options must be used in conjunction with the associated system and may not be compatible with other options or accessories. Please refer to the following: (B) Consult Enlighted system pages for additional details and compatibility. | Notes (1) An EQ Grid Clip is recommended for all 9'16" ceiling systems. Four required per fixture. (17) Accessories sold separately will be separately analyzed under domestic preference requirements. Consult factory for further information. Integrated options must be used in conjunction with the associated system and may not be compatible with other options or accessories. Please refer to the following: (D) Consult SVPD series system pages for additional details and compatibility. (18) For Anti-microbial matte white finish, replace W with AMW. ex. DFCL-2448AMW-U |

Product Specifications

Construction

- Formed steel housing with integral Grid-lock feature and optional grid security clips

Integrated Controls

- Standard with 0-10V dimming. Optionally available with Lutron and Dali

LED and Light Engine

- Available in 3000, 3500, 4000, and 5000K fixed color temperatures, or with VividTune white tuning technology
- Drivers available in 120-277V and 347V
- TM21 life at 60,000 hours up to L85 and L70 exceeds 132,000 hours

Emergency Battery Options

- Optional 120-277V emergency battery available in 7W or 14W
- 90-minute backup period for code compliance
- Test switch with laser pointer and testing from floor feature for ease of use
- Generator transfer options available

Finish

- High Gloss white finish standard

Shielding

- Standard ribbed frosted acrylic curved diffuser
- Optional clear curved diffuser with perf or decorative pattern inserts
- Optional smooth acrylic frosted curved lens (S)
- Optional metal perforated acrylic curved lens (RDP)
- Optional High-Efficiency Curved Round Perf Inlay (HRP)
- Optional square frosted acrylic lens (SQR)

Compliance


- IC rated, cULus Wet Location
- RoHS compliant
- ISO5-9 certified
- IP65
- IK10 - Polycarbonate Lens
- NSF rated; Splash, Non-Food Zone - Typical rating for lighting equipment not subjected to direct food contact. (e.g. ceiling mount luminaires). Examples of equipment subjected to direct food contact would be cutting boards, work-tables, mixers, can-openers, other)

Warranty


- Five year warranty standard

Photometric Data

[View IES files](#)



Cross Section



Energy and Performance Data

Shielding

| Lumen Adjustment Factors | | | |
|--------------------------|------|------|------|
| S | RDP | HRP | SQR |
| 1.05 | 0.67 | 0.85 | 0.96 |

Lumen Calculator

| CCT Multiplier | 80 CRI | 90 CRI |
|----------------|--------|--------|
| 3000K | 0.994 | 0.830 |
| 3500K | 1.00 | 0.845 |
| 4000K | 1.00 | 0.854 |
| 5000K | 1.065 | 0.852 |

Lumen Maintenance

| Version | TM-21 Lumen Maintenance (60,000 hours) ⁽¹⁾ | Theoretical L70 (Hours) ⁽²⁾ |
|----------------------|---|--|
| Standard | > 87% | > 162,000 |
| High Efficiency | > 94% | > 290,000 |
| Very High Efficiency | > 94% | > 290,000 |

Notes: (1) Supported by IES TM-21 standards. (2) Theoretical values represent estimations commonly used; however, refer to the IES position on LED Product Lifetime Prediction, IES PS-10-18, that explains proper use of IES TM-21 and LM-80.

Load Data (Stock Product)

| | |
|-----------------|-------|
| THD | 6% |
| Power Factor | 0.99 |
| Weight (lbs.) | 16 |
| Low Temp. Start | -20°C |

Shipping Data

| Catalog No. | Wt. | Pallet 49"L x 52"W x 46"H |
|-------------|-----------|------------------------------|
| 2' x 4' | 20.4 lbs. | 28 |

Energy and Performance Data Catalog Number

Standard Efficacy Versions – Single Row of LEDs

| Catalog Number | Watts | CA08 | LPW | CA125 | LPW | CP125 | LPW | CP187 | LPW | CP250 | LPW |
|---------------------------|-------|------|-----|-------|-------|-------|-------|-------|-------|-------|-------|
| 24FCZ2-30-XXXX-UNV-35-CD1 | 24.2 | 2930 | 121 | 2920 | 120.6 | 2863 | 118.3 | 2742 | 113.3 | 2719 | 112.4 |
| 24FCZ2-35-XXXX-UNV-35-CD1 | 30.1 | 3516 | 117 | 3504 | 116.4 | 3435 | 114.1 | 3290 | 109.3 | 3263 | 108.4 |
| 24FCZ2-40-XXXX-UNV-35-CD1 | 36.2 | 4056 | 112 | 4041 | 111.6 | 3963 | 109.5 | 3795 | 104.8 | 3764 | 104.0 |
| 24FCZ2-45-XXXX-UNV-35-CD1 | 42.9 | 4463 | 104 | 4447 | 104 | 4361 | 102 | 4176 | 97 | 4142 | 97 |
| 24FCZ2-50-XXXX-UNV-35-CD1 | 48.6 | 4847 | 100 | 4830 | 99 | 4736 | 97 | 4535 | 93 | 4498 | 93 |
| 24FCZ2-55-XXXX-UNV-35-CD1 | 50.5 | 5385 | 107 | 5365 | 106 | 5261 | 104 | 5039 | 100 | 4997 | 99 |
| 24FCZ2-60-XXXX-UNV-35-CD1 | 55.6 | 5840 | 105 | 5819 | 105 | 5706 | 103 | 5464 | 98 | 5420 | 97 |
| 24FCZ2-65-XXXX-UNV-35-CD1 | 62.8 | 6352 | 101 | 6329 | 101 | 6206 | 99 | 5944 | 95 | 5895 | 94 |

High Efficacy Versions – Two Rows of LEDs

| Catalog Number | Watts | CA08 | LPW | CA125 | LPW | CP125 | LPW | CP187 | LPW | CP250 | LPW |
|-----------------------------|-------|------|-----|-------|-----|-------|-----|-------|-----|-------|-----|
| 24FCZ2-30HE-XXXX-UNV-35-CD1 | 22.4 | 2913 | 130 | 2902 | 130 | 2846 | 127 | 2725 | 122 | 2703 | 121 |
| 24FCZ2-35HE-XXXX-UNV-35-CD1 | 26.9 | 3463 | 129 | 3450 | 128 | 3383 | 126 | 3240 | 120 | 3214 | 119 |
| 24FCZ2-40HE-XXXX-UNV-35-CD1 | 30.6 | 3894 | 127 | 3880 | 127 | 3805 | 124 | 3644 | 119 | 3614 | 118 |
| 24FCZ2-45HE-XXXX-UNV-35-CD1 | 35.3 | 4428 | 125 | 4412 | 125 | 4326 | 123 | 4143 | 117 | 4110 | 116 |
| 24FCZ2-50HE-XXXX-UNV-35-CD1 | 38.6 | 4853 | 126 | 4836 | 125 | 4741 | 123 | 4541 | 118 | 4504 | 117 |
| 24FCZ2-55HE-XXXX-UNV-35-CD1 | 43.5 | 5378 | 124 | 5359 | 123 | 5254 | 121 | 5032 | 116 | 4991 | 115 |
| 24FCZ2-60HE-XXXX-UNV-35-CD1 | 44.1 | 5809 | 132 | 5789 | 131 | 5676 | 129 | 5436 | 123 | 5392 | 122 |
| 24FCZ2-65HE-XXXX-UNV-35-CD1 | 48.9 | 6369 | 130 | 6347 | 130 | 6223 | 127 | 5960 | 122 | 5911 | 121 |
| 24FCZ2-70HE-XXXX-UNV-35-CD1 | 51.0 | 6783 | 133 | 6758 | 133 | 6627 | 130 | 6347 | 124 | 6295 | 123 |
| 24FCZ2-75HE-XXXX-UNV-35-CD1 | 55.4 | 7318 | 132 | 7292 | 132 | 7150 | 129 | 6848 | 124 | 6792 | 123 |


Very High Efficacy Versions – Three Rows of LEDs

| Catalog Number | Watts | CA08 | LPW | CA125 | LPW | CP125 | LPW | CP187 | LPW | CP250 | LPW |
|-------------------------------|-------|-------|-----|-------|-----|-------|-----|-------|-----|-------|-----|
| 24FCZ2-30VHE-XXXX-UNV-35-CD1 | 20.4 | 2910 | 143 | 2900 | 142 | 2843 | 139 | 2843 | 139 | 2701 | 132 |
| 24FCZ2-35VHE-XXXX-UNV-35-CD1 | 22.8 | 3408 | 150 | 3396 | 149 | 3330 | 146 | 3330 | 146 | 3163 | 139 |
| 24FCZ2-40VHE-XXXX-UNV-35-CD1 | 26.2 | 3906 | 149 | 3893 | 149 | 3817 | 146 | 3817 | 146 | 3625 | 138 |
| 24FCZ2-45VHE-XXXX-UNV-35-CD1 | 29.6 | 4406 | 149 | 4390 | 148 | 4305 | 145 | 4305 | 145 | 4089 | 138 |
| 24FCZ2-50VHE-XXXX-UNV-35-CD1 | 32.7 | 4894 | 150 | 4877 | 149 | 4782 | 146 | 4782 | 146 | 4542 | 139 |
| 24FCZ2-55VHE-XXXX-UNV-35-CD1 | 36.1 | 5383 | 149 | 5364 | 149 | 5260 | 146 | 5260 | 146 | 4996 | 138 |
| 24FCZ2-60VHE-XXXX-UNV-35-CD1 | 38.7 | 5852 | 151 | 5831 | 151 | 5718 | 148 | 5718 | 148 | 5431 | 140 |
| 24FCZ2-65VHE-XXXX-UNV-35-CD1 | 42.2 | 6345 | 150 | 6322 | 150 | 6199 | 147 | 6199 | 147 | 5888 | 140 |
| 24FCZ2-70VHE-XXXX-UNV-35-CD1 | 45.7 | 6822 | 149 | 6798 | 149 | 6666 | 146 | 6666 | 146 | 6332 | 139 |
| 24FCZ2-75VHE-XXXX-UNV-35-CD1 | 49.9 | 7405 | 148 | 7379 | 148 | 7235 | 145 | 7235 | 145 | 6872 | 138 |
| 24FCZ2-80VHE-XXXX-UNV-35-CD1 | 53.8 | 7855 | 146 | 7827 | 146 | 7675 | 143 | 7675 | 143 | 7290 | 136 |
| 24FCZ2-85VHE-XXXX-UNV-35-CD1 | 57.9 | 8312 | 144 | 8282 | 143 | 8121 | 140 | 8121 | 140 | 7714 | 133 |
| 24FCZ2-90VHE-XXXX-UNV-35-CD1 | 61.8 | 8749 | 142 | 8718 | 141 | 8549 | 138 | 8549 | 138 | 8120 | 131 |
| 24FCZ2-95VHE-XXXX-UNV-35-CD1 | 65.6 | 9202 | 140 | 9169 | 140 | 8990 | 137 | 8990 | 137 | 8540 | 130 |
| 24FCZ2-100VHE-XXXX-UNV-35-CD1 | 69.6 | 9849 | 142 | 9814 | 141 | 9623 | 138 | 9623 | 138 | 9141 | 131 |
| 24FCZ2-110VHE-XXXX-UNV-35-CD1 | 77.4 | 10726 | 139 | 10688 | 138 | 10480 | 135 | 10480 | 135 | 9954 | 127 |
| 24FCZ2-120VHE-XXXX-UNV-35-CD1 | 83.6 | 11802 | 141 | 11759 | 141 | 11531 | 138 | 11531 | 138 | 10953 | 131 |
| 24FCZ2-130VHE-XXXX-UNV-35-CD1 | 90.7 | 12826 | 141 | 12780 | 141 | 12532 | 138 | 12532 | 138 | 11903 | 131 |
| 24FCZ2-150VHE-XXXX-UNV-35-CD1 | 104.2 | 14503 | 139 | 14451 | 139 | 14170 | 136 | 14170 | 136 | 13460 | 129 |
| 24FCZ2-170VHE-XXXX-UNV-35-CD1 | 123.4 | 16450 | 133 | 16392 | 133 | 16073 | 130 | 16073 | 130 | 15267 | 124 |



24 FCZ LED with VividTune Tunable White

VividTune tunable white luminaires from Cooper Lighting Solutions deliver high-quality light in a broad range of continuously variable color temperatures and intensities. Create a dynamic environment by adjusting the ambient light warmer or cooler to influence mood, support the task at hand, or create a dramatic ambience. The ability to control correlated color temperature and intensity separately using simple controls is the next evolution of LED lighting for the commercial, educational, healthcare and hospitality space. The unparalleled flexibility and number of available lighting environments enable users to find the right light with tunable white.



Performance Data*

| Tunable White - Lumen Adjustment Factors | | | | |
|--|-------------|--------|-------------|--------|
| CCT | 3000K-5000K | | 2700K-6500K | |
| | 80 CRI | 90 CRI | 80 CRI | 90 CRI |
| 2700K | - | - | 0.878 | 0.750 |
| 3000K | 0.904 | 0.744 | 0.903 | 0.779 |
| 3500K | 0.956 | 0.813 | 0.934 | 0.819 |
| 4000K | 1.004 | 0.878 | 0.954 | 0.844 |
| 4500K | 1.014 | 0.893 | 0.972 | 0.866 |
| 5000K | 1.014 | 0.893 | 0.985 | 0.884 |
| 6500K | - | - | 0.999 | 0.908 |

| 2' x 4' FCZ LED - Example of Approximate Lumen Calculation | | | |
|--|----------------------------|-------------------------------|-------------------------------|
| | Standard Catalog # | VividTune 80 CRI Catalog # | VividTune 90 CRI Catalog # |
| CCT Setting | 24FCZ2-40HE-UNV-L835-CD1-U | 24FCZ2-40HE-UNV-L83050-W2A1-U | 24FCZ2-40HE-UNV-L93050-W2A1-U |
| 3000K | - | 3641 | 2998 |
| 3500K | 4029 | 3853 | 3275 |
| 4000K | - | 4046 | 3537 |
| 4500K | - | 4084 | 3599 |
| 5000K | - | 4084 | 3599 |

Controlling VividTune Tunable White

VividTune luminaires make tunable white more accessible by using simple and familiar controls. From wall dimmers to wireless controls, VividTune tunable white luminaires are compatible with industry standard 0-10V dimming controls. A single 0-10V dimming input is used to control intensity (brightness) while a second 0-10V dimming input is used to adjust CCT. For suggested control configurations, go to www.cooperlighting.com for tunable white application guides.

