Selection Guide

Market focused portfolio with products designed for broad applications

Value - competitive pricing in the industry

Performance market leading
performance with
industry ratings
and certifications
to meet the most
stringent application
requirements











ı			Good		Better Better			Best
Click on products to learn more								
١,			B95	H12	G12	TR11	TR15	FW
	APPLICABILITY ¹	Behavioral Health	**	**	**	***		***
		Outdoor Vandal Resistant	***	***	***	***		***
		Indoor Vandal Resistant	**	**	**	***		**
		Industrial High Abuse	***	***	***	***		***
		Multifamily homes	**	**	**	***		***
	MOUNTING	Wall	·	~	✓	~		✓
		Ceiling	v	v	✓	~		N/A
	FEATURES	Size	5" x 9" Rectangle	12" x 12" Square	12" x 12" Square	11" Round	15" Round	6" x 12", 12" x 6", 9" x 9", 12" x 12"
		Maximum Lumen Output	1,975	4,703	3,750	2,630	4,875	2,500
		Lens Thickness	0.130"	0.156"	0.130"	0.125"		0.125"
		Emergency	N/A	Optional	Optional	Optional		Optional
		Occupancy	N/A	Optional	Optional	Optional		Optional
		Photocell	Optional	Optional	Optional	Optional		N/A
	CERTIFICATIONS	IP	IP65	IP65	IP65	IP65		IP65
		Wet Location	Standard	Standard	Standard	Standard		Standard

Notes: 1. ★ ★ ★ = high applicability, ★ ★ = medium applicability, ★ = low applicability, blank = non-applicable

