

| | | | | | |
|-------------|--|-----------|--|------|--|
| Project | | Catalog # | | Type | |
| Prepared by | | Notes | | Date | |



Fail-Safe

Vaportite LED

4' Tamper Resistant LED Vaportite

Typical Applications

Parking Garage • Cold Storage • Canopy • Warehouse • Food Processing • Manufacturing • Complex Environments

Interactive Menu

- Order Information [page 2](#)
- Photometric Data [page 2](#)
- Product Warranty

Product Certification




Product Features




Top Product Features

- 2ft, 4ft, and 8ft Sealed and Gasketed Tamper Resistant Vaportite
- Lumen packages up to 22K lumens
- High-Performance efficacy up to 150 LPW
- LEDs available in 3500K, 4000K and 5000K at 80 CRI
- Rated for -40c to 35c ambient
- Options to meet Buy American and other domestic preference requirements

Dimensional and Mounting Details



Installation Data



MOUNTING BRACKETS
Furnished
Two per 2' and 4' Unit
Four per 8' Unit




OPTIONAL CHAN HANGING SET
(VT2-CHAIN/SET-U)
Includes 6 ft. of chain, 4 large S-Hooks and 4 small S-Hooks
Order One (1) Kit for each 2' or 4' Fixture

Order Information

SAMPLE ORDER NUMBER: **4VRVT2-LD5-4-DR-UNV-L840-CD1-WL-U**

| Domestic Preferences | Series | Lamp Type | LED Lumens Output | Lens | Distribution | Voltage | Remote Emergency Enclosure |
|--|--|---------------------|--|--|--|---------------------------------------|--|
| Domestic Preferences ⁽³⁾ | Series | Lamp Type | LED Lumens Output | Lens | Distribution | Voltage | Remote Emergency Enclosure |
| [Blank] =Standard BAA =Buy American Act TAA =Trade Agreements Act | 4VRVT2 =4' Tamper Resistant Vaportite | LD5 =LED 5.0 | 4=4000 Lumens 6=6000 Lumens 8=8000 Lumens 11=11000 Lumens | DR =Internal Prismatic Lens/15% DR High Impact Additive DR100 =Internal Prismatic Lens/100% DR High Impact Additive FR50 =Frosted Lens/15% DR High Impact Additive ⁽¹⁾ | [Blank] =Medium (Standard) W =Wide Distribution | UNV =Universal Voltage 120-277 | EL10W =10-watt, 120-277V emergency battery pack installed ⁽²⁾ VT-REM-EL =Remote Emergency Installed, 700 lumens ⁽²⁾ |
| Notes (3) Only product configurations with these designated prefixes are built to be compliant with the Buy American Act of 1933 (BAA) or Trade Agreements Act of 1979 (TAA), respectively. Please refer to DOMESTIC PREFERENCES website for more information. Components shipped separately may be separately analyzed under domestic preference requirements | | | | Notes (1) Not available in wide distribution. | | | Notes (2) EL must specify 120 or 277V only. |

| Lamps | Driver Type | Label | Options | Packaging | Accessories |
|---|--|-------------------------------|---|---------------------|--|
| Lamps | Driver Type | Label | Options | Packaging | Accessories (order separately) ⁽⁴⁾ |
| L835 =3500K, LED L840 =4000K, LED L850 =5000K, LED L652 =Green 520nm LED LA59 =Amber 590nm LED LR63 =Red 630nm LED | CD1 =1 Dimming Driver SLTD1 =Fifth Light DALI | WL =Wet Location Label | SSL =Stainless Steel Latches GL =Single Element Fuse TH =(2) Top Watertite Hubs TEH =(2) Top and (2) End Watertite Hubs (all Watertite Hubs have 1/2" Conduit Entry) MS =Damp Listed Motion Sensor MSWL20 =Wet Listed Motion Sensor, max 20ft mounting height HBE11 =Wet location PIR Indoor/Outdoor Occupancy Sensor ⁽¹⁾ | U =Unit Pack | VT2-Chain/Set-U =Chain Hanging Set. Includes 6 ft. of chain, 4 large S-Hooks and 4 small S-Hooks Order One (1) Kit for each 2' or 4' Fixture VT2-SS-MBK =Stainless Steel Mounting Bracket  |
| | | | Notes (1) Available for 120V, 277V, and 347V voltage only. | | Notes (4) Accessories sold separately will be separately analyzed under domestic preference requirements. Consult factory for further information. |

Product Specifications

Construction

- Rugged and durable construction
- Fiberglass housing is reinforced polyester and self-extinguishing (ASTM-D635-74) plastic
- Full metal fixture liner
- Watertight housing
- 1/2" conduit entry at each end of housing (standard) for continuous feed
- Polyurethane gasketing provides a continuous seamless seal for the diffuser lens
- Four sturdy cam latches clamp diffuser tightly for a positive seal between housing, gasketing and diffuser
- Surface or chain mounting
- Torx (R) Tamperproof Screws to prevent unauthorized access

Electrical

- Long-Life LED system coupled with electrical driver for optimal performance
- LED's available in 3500K, 4000K and 5000K with a CRI ≥ 80
- Projected life is 60,000 hours at 91% lumen output
- Electronic drivers are available for 120-277V applications
- 0-10V dimming control (standard)
- Operating temperature of -40°C to 35°C; Ideal for cold storage environments

Lens

- High-impact diffuser lens
- Internal Prismatic Lens with 15% DR High Impact Additive (DR) or Internal Prismatic Lens with 100% DR High Impact Additive (DR100)
- Frosted Lens with 15% DR High Impact Additive (FR50) option

Finish

- Housing is permanent pearl gray color

Warranty


- Five-year limited warranty

Compliance


- UL/cUL listed for Wet location
- RoHS compliant
- LED modules comply with IESNA LM-79 and LM-80 standards

Photometric Data

 [View IES files](#)



4VRVT2-LD5-6-DR-UNV-L840-CD1-WL-U
Electronic Driver
Linear LED 4000K
Spacing criterion: (H) 1.21 x mounting height,
(L) 1.22 x mounting height
Lumens: 6197
Input Watts: 50.6W
Efficacy: 122.5 lm/W
Test Report:
4VRVT2-LD5-6-DR-UNV-L840-CD1-WL-U.IES



4VRVT2-LD5-6-DR-W-UNV-L840-CD1-WL-U
Electronic Driver
Linear LED 4000K
Spacing criterion: (H) 1.22 x mounting height,
(L) 1.6 x mounting height
Lumens: 5931
Input Watts: 50.6W
Efficacy: 117.2 lm/W
Test Report:
4VRVT2-LD5-6-DR-W-UNV-L840-CD1-WL-U.IES

Energy and Performance Data

Color LED

| Catalog Number | Description | Delivered Lumens | | | | | Watts | Efficacy | | | | |
|------------------------------------|--|------------------|------|-------|---------|------|-------|----------|------|-------|---------|------|
| | | Lensing | | | | | | Lensing | | | | |
| | | DR | DR-W | DR100 | DR100-W | FR50 | | DR | DR-W | DR100 | DR100-W | FR50 |
| 4VRVT2-LD5-4-XX-UNV-LR63-CD1-WL-U | 4ft, Vaportight, 4000 lumens UNV, Red 630nm | 663 | 634 | 663 | 636 | 656 | 77 | 9 | 8 | 9 | 8 | 9 |
| 4VRVT2-LD5-4-XX-UNV-LA59-CD1-WL-U | 4ft, Vaportight, 4000 lumens UNV, Amber 590nm | 1159 | 1110 | 1160 | 1112 | 1148 | 46 | 25 | 24 | 25 | 24 | 25 |
| 4VRVT2-LD5-4-XX-UNV-LG52-CD1-WL-U | 4ft, Vaportight, 4000 lumens UNV, Green 520nm | 3313 | 3170 | 3315 | 3178 | 3280 | 71 | 47 | 45 | 47 | 45 | 46 |
| 4VRVT2-LD5-6-XX-UNV-LR63-CD1-WL-U | 4ft, Vaportight, 6000 lumens UNV, Red 630nm | 992 | 949 | 992 | 951 | 982 | 131 | 8 | 7 | 8 | 7 | 7 |
| 4VRVT2-LD5-6-XX-UNV-LA59-CD1-WL-U | 4ft, Vaportight, 6000 lumens UNV, Amber 590nm | 1735 | 1661 | 1737 | 1665 | 1718 | 77 | 23 | 22 | 23 | 22 | 22 |
| 4VRVT2-LD5-6-XX-UNV-LG52-CD1-WL-U | 4ft, Vaportight, 6000 lumens UNV, Green 520nm | 4958 | 4745 | 4962 | 4756 | 4909 | 120 | 41 | 40 | 41 | 40 | 41 |
| 4VRVT2-LD5-8-XX-UNV-LR63-CD1-WL-U | 4ft, Vaportight, 8000 lumens UNV, Red 630nm | 1317 | 1219 | 1319 | 1219 | 1300 | 152 | 9 | 8 | 9 | 8 | 9 |
| 4VRVT2-LD5-8-XX-UNV-LA59-CD1-WL-U | 4ft, Vaportight, 8000 lumens UNV, Amber 590nm | 2304 | 2133 | 2308 | 2133 | 2275 | 90 | 26 | 24 | 26 | 24 | 25 |
| 4VRVT2-LD5-8-XX-UNV-LG52-CD1-WL-U | 4ft, Vaportight, 8000 lumens UNV, Green 520nm | 6584 | 6094 | 6593 | 6095 | 6500 | 139 | 47 | 44 | 47 | 44 | 47 |
| 4VRVT2-LD5-11-XX-UNV-LR63-CD1-WL-U | 4ft, Vaportight, 11000 lumens UNV, Red 630nm | 1721 | 1593 | 1723 | 1593 | 1699 | 214 | 8 | 7 | 8 | 7 | 8 |
| 4VRVT2-LD5-11-XX-UNV-LA59-CD1-WL-U | 4ft, Vaportight, 11000 lumens UNV, Amber 590nm | 3012 | 2788 | 3016 | 2788 | 2974 | 126 | 24 | 22 | 24 | 22 | 24 |
| 4VRVT2-LD5-11-XX-UNV-LG52-CD1-WL-U | 4ft, Vaportight, 11000 lumens UNV, Green 520nm | 8606 | 7966 | 8617 | 7966 | 8496 | 196 | 44 | 41 | 44 | 41 | 43 |

Lumen Maintenance

| Ambient Temperature | TM-21 Lumen Maintenance (60,000 hours) | Theoretical L70 (Hours) |
|---------------------|--|-------------------------|
| 25°C | > 91% | > 237,000 |

Shipping Data

| Catalog No. | Wt. |
|-------------|---------|
| 4VRVT2-LD5 | 18 lbs. |

Input Watts:

| |
|-----------------------------------|
| 4VRVT2-LD5-4 (4,000 lumens)=30W |
| 4VRVT2-LD5-6 (6,000 lumens)=51W |
| 4VRVT2-LD5-8 (8,000 lumens)=58W |
| 4VRVT2-LD5-11 (11,000 lumens)=82W |