

## **EXTERIOR LED SOLUTIONS**

Date:	Project:	Туре:	Notes:	Catalog #:

## WF-AO SERIES Adjustable LED Full Cut-off Wall Pack

Rev: 12-2022

The WP-AO Series is great for commercial and industrial applications. Adjustable output options makes the WP-AO the ideal choice for illuminating building perimeters where control of spill light is important.

#### **Applications**

Ideal for use in exterior commercial and industrial building perimeters.

#### Construction

Housing made from die-cast aluminum. Tempered glass lens.

#### Mounting

Wall Mount.

#### **Electrical**

Utilizes high-efficiency LED power supply and circuit boards. 120-277V & 0-10V dimming standard. 50/60HZ input frequency. 5KV Surge Protection.

#### **Operating Temperature**

Suitable for -40°C - 40°C Ambient

#### CRI

70+

#### Finish

Standard in dark bronze.

#### **Lumen Maintenance**

L70 rating of 54,000

#### Warranty

Five-year warranty. Terms and Conditions Apply. See warranty documentation for more information.

#### Certification

UL Wet Listed. Adheres to LM79, LM80 and TM21 industry standards. DesignLights Consortium® (DLC) 5.1 Premium listed¹. IP65 Rated.

















# **EXTERIOR LED SOLUTIONS**

## **Catalog Ordering**

Sample Part #WF-S-3L-AO-40K

Series	Size & Lumens	Туре	Color Temp (CCT)	Finish	Controls
WF					
WF	<b>S-3L</b> (Small / 15W-22W-28W)	AO (Adjustable Output)	<b>30K</b> (3000 Kelvin Temp) <b>40K</b> (4000 Kelvin Temp) <b>50K</b> (5000 Kelvin Temp)	Blank (Standard Dark Bronze)	<b>OSW</b> (Wet Location Occupancy Sensor)

### Performance Data

FSC Part #	Form Factor	Rated Wattage	Kelvin Temp	Delivered Lumens	Efficacy	CRI	Replaces
		15	3000	2118	141	>70	
	) Small	15	4000	2162	145	>70	2 x 13W Compact Fluorescent
		15	5000	2184	145	>70	
		22	3000	2918	132	>70	
WF-S-3L-AO		22	4000	2980	138	>70	2 x 18W Compact Fluorescent
		22	5000	3009	136	>70	
		28	3000	3289	121	>70	
		28	4000	3602	133	>70	50W High Pressure Sodium
		28	5000	3568	132	>70	

### **Electrical Data**

Drivers: 120-277V WF (Small)

15W: 120V: 0.1245A, 277V: 0.0733A 22W: 120V: 0.1804A, 277V: 0.0954A 28W: 120V: 0.2264A, 277V: 0.1019A




# **EXTERIOR LED SOLUTIONS**

## **Physical Characteristics**


#### **Dimensions**

Version	Depth	Length	Width	Weight
Small	3.6"	7.63"	5.75"	4lbs


Front View




Side View



**Back View** 



**Bottom View** 



### **Notes**

1 Not all versions of this product may be DLC Premium qualified or DLC qualified. Please check the DLC Qualified Products List at <a href="www.designlights.org/">www.designlights.org/</a> to confirm which versions are qualified.