













Gardco features a range of square and round poles suitable for site and area lighting.



| Family | SSS or L/SSS | SRS or L/SRS | GTS | TRS | SSA or Legacy SSA | SRA or Legacy RA | TRA or Legacy TRA |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description | Straight Square Steel | Straight Round Steel | Tapered Square Steel | Tapered Round Steel | Straight Square Aluminum | Straight Round Aluminum | Tapered Round Aluminum |
| Nominal Height (ft) | 10, 12, 14, 15, 18, 20, 25, 30, 35, 40 | 10, 12, 14, 16, 20, 25, 30 | 20, 25, 30, 35, 39 | 20, 25, 30, 35, 39 | 8, 10, 12, 15, 16, 18, 20, 25, 30 | 8, 10, 12, 15, 16, 18, 20, 25, 30 | 8, 10, 12, 14, 16, 20, 25, 28, 30, 35, 39 |
| Diameter (inches) | 4, 5, 6 | 3, 4, 5 | 3.05 x 5.25, 3.25 x 6.00, 3.11 x 6.41, 2.96 x 6.81, 2.92 x 7.18, 2.87 x 7.13 | 3.1 x 5.9, 3.7 x 6.5, 2.4 x 5.9, 3.5 x 7.0, 2.4 x 6.6, 3.8 x 8.0, 2.4 x 7.3, 3.6 x 8.5, 2.4 x 7.8, 3.6 x 9.0 | 4, 5, 6 | 4, 5 | 3 x 4, 3 x 5, 4 x 6, 4 x 7, 4.5 x 8, 5 x 8, 6 x 10 |
| Wall Thickness/Gauge | 11 ga., 7 ga. | 11 ga., 7 ga. | 11 ga., 7 ga. | 11 ga. | .125", .156", .188", .250" | .125", .156", .188" | .125", .156", .188", .250" |
| Base | Cast Base | | | | Cast Base Steel Tenon Base Hinged Base | Cast Base Steel Tenon Base Hinged Base | Cast Base Hinged Base |
| Bolt Circle (inches) | 8.5, 11, 12 (+/- 0.5) | 8.5 (+/- 0.5) | 10.75, 12, 12.5, 13, 13.5 | 9, 9.5, 10, 10.5, 11, 11.5, 12.5 | 7, 9, 10, 11, 12 | 6.5 - 10 (varies) | 6.5 - 14.5 (varies) |
| EPA 80 MPH | 4.7 - 30.6 | 2.8 - 19.1 | 8.6 - 18.0 | 10.7 - 24.2 | 2.2 - 42.5 | 1.2 - 20.2 | 5.8 - 36.0 |
| EPA 90 MPH | 2.0 - 23.9 | 1.9 - 15.0 | 5.4 - 13.8 | 8.5 - 19.3 | N/A - 32.7 | N/A - 15.7 | 4.0 - 27.9 |
| EPA 100 MPH | N/A - 18.9 | 1.3 - 12.2 | 3.0 - 10.7 | 6.6 - 15.6 | N/A - 25.8 | N/A - 12.6 | 2.8 - 22.2 |
| EPA 110 MPH | N/A - 14.5 | - | N/A - 8.4 | 5.5 - 13.0 | - | - | 1.7 - 17.9 |
| EPA 120 MPH | N/A - 12.0 | - | N/A - 6.5 | 4.5 - 11.0 | - | - | 1.2 - 14.7 |
| EPA 130 MPH | N/A - 9.9 | - | N/A - 5.1 | 3.5 - 9.3 | - | - | 0.9 - 12.1 |
| Options | Duplex Receptacle, Ground Fault Receptacle, Festoon Outlet, Vibration Dampener, Additional Hand Hole, Couplings (Internal Thread), Nipples (External Thread) | | | | | | |
| Finish | Bronze, Black, White, Medium Grey, Dark Grey, Galvanized, Lumec GY3, SolarForm Dark Grey (RAL 7011), Finish over Galvanized, Optional (e.g. RAL code), Special (custom color chip) | | | | Bronze, Black, White, Medium Grey, Dark Grey, Lumec GY3, SolarForm Dark Grey (RAL 7011), Optional (e.g. RAL code), Special (custom color chip) | | |
| Limited Warranty | 3 Year: SSS and SRS, 1 Year: L/SSS, L/SRS, GTS and TRS | | | | 5 Year: SSA, SRA and TRA, 1 Year: Legacy SSA, Legacy RA and Legacy TRA | | |
| Link |  |  |  |  |    |    |   |