
Copper Pathlyte (GAL3) Specification Sheet

Project Name:	Location:	MFG: Philips Hadco
Fixture Type:	Catalog No.:	Qty:



Ordering Guide

Example: GAL3 AC S7

Product Code	GAL3	Copper Pathlyte
Finish	AC	Hand-Crafted Copper
Mounting	S7	Mounting Stake

Spacing Chart

Specifications

HOUSING:

Solid copper square extrusion with solid copper end and brass fitter. ½" NPS male threads to screw onto accessory mounting stake or junction box, sold separately.

FINISH

Natural Copper is bright polished, untreated copper. Color will age naturally to a fine dark copper patina.

OPTICAL ASSEMBLY:

Reflector is Stainless Steel.

LAMPING:

10W wedge base T3 ¼ (xenon) lamp is included with fixture. 12W maximum wedge base T3-¼ lamp. Lower wattage lamps are acceptable.

ELECTRICAL ASSEMBLY:

Wedge base socket type (T3-% or T5). Socket is hinged for easy relamping. 12 Volt fixture is pre-wired with 3-ft pigtail of 18-2 AWG, 105° C, SPT-1W wire. Low voltage quick connector, catalog #LVC3 included for easy hook-up to the low voltage supply cable, not included. 12 Volt system requires remote transformer, not included.

WARRANTY:

Ten-year limited warranty.

CERTIFICATIONS:

ETL listed to U.S. safety standards for wet locations. cETL listed to Canadian safety standards for wet locations. Manufactured to ISO 9001:2008 Standards.

Height:

22 3/8" (568mm)

Width:

6 1/8" (156mm)

Max. Weight:

3.8 lb

ISO 9001:2008 Registered Page 1 of 1



Note: Philips reserves the right to modify the above details to reflect changes in the cost of materials and/or production and/or design without prior notice. 100 Craftway Drive, Littlestown, PA 17340 | P: +1-717-359-7131 F: +1-717-359-9289 | http://www.hadco.com | Copyright 2013 Philips HW2