

Landscape Transformers



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- LARGE SECONDARY CONNECTION BLOCK FOR EASY WIRING
- 1/8" STAINLESS STEEL NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- COMES STANDARD WITH 6 FOOT PRIMARY LINE CORD
- MULTI-VOLT SECONDARY UP TO 15 VOLTS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.
- TIMER AND PHOTOCELL READY. SOLD SEPARATELY.

REQUIREMENTS

- MEETS OR EXCEEDS THE UL STANDARD 1838 FOR LANDSCAPE LIGHTING
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME



150 WATT

300 WATT

PART NUMBER
PRIMARY VOLTAGE
OUTPUT VOLTAGE
BREAKERS
FREQUENCY
DIMENSIONS
WEIGHT

1023-12-SS
120VAC-1A MAX
12, 13, 14, 15 VAC
1x15A
60 Hz
15-1/4" x 4-3/4" x 5-1/2"
15 LBS.

1101-12-SS
120VAC-3A MAX
12, 13, 14, 15 VAC
1x25A
60 Hz
17" x 7-1/2" x 5-1/2"
20 LBS.