

PROJECT	DATE
ТҮРЕ	CATALOG #

20W COHIBA


POWER FLOOD LED-FL-115B-20W

KEY FEATURES

INTEGRATED LED WITH HIGH LUMEN OUTPUT
QUICK CHANGE LED TECHNOLOGY ALLOWS FOR EASY REPLACEMENT OF LED BOARD IN THE FIELD
DIMMABLE*
HEAVY CAST BRASS
NATURAL BRONZE FINISH GUARANTEED NOT TO CHIP, FLAKE OR PEEL
TEMPERED PRISMATIC LENS
PRODUCT SPECIFICATIONS

DIMENSIONS	4"H X 5-1/4"W X 5-3/4"D
MATERIAL	CAST BRASS
LENS	TEMPERED PRISMATIC LENS
LED	20W SMD
LUMENS	1050
VOLTAGE	11-13V AC/DC
PROJECTION	UP TO 50 FT
LEAD WIRE	3 FT

FIXTURE CONFIGURATION



*PRIMARY SIDE DIMMING: Requires LED magnetic low voltage (MLV) or LED electronic low voltage (ELV) dimmable transformer and compatible LED dimmer (MLV or ELV) For more information see installation guidelines + Fully tested with Lutron Diva (DVLV-600P) dimmer and Lightcraft dimmable transformers

LIGHTCRAFT OUTDOOR | 9811 OWENSMOUTH AVE | UNIT 1 | CHATSWORTH, CA 91311 PHONE: 818.349.2663 | FAX: 818.349.2676 | E-MAIL: SALES@LIGHTCRAFTOUTDOOR.COM

NOTES



PROJECT	DATE
ТҮРЕ	CATALOG #

FEATURES



HIGH QUALITY HEAT SINK

QUICK CHANGE TECHNOLOGY

T ALLOWS EMENT OF REMOVE THESE 4 SCREWS TO RELEASE THE LED BOARD

QUICK DISCONNECT ALLOWS FOR EASY REPLACEMENT OF LED BOARD

See LED-FL-115B INSTALLATION SHEET for full detailed installation instructions.

LIGHTCRAFT OUTDOOR | 9811 OWENSMOUTH AVE | UNIT 1 | CHATSWORTH, CA 91311 PHONE: 818.349.2663 | FAX: 818.349.2676 | E-MAIL: SALES@LIGHTCRAFTOUTDOOR.COM

2