



PROJECT	DATE
TYPE	CATALOG #

MASONRY LIGHT 13

LED-ML-13-ADJ

KEY FEATURES

- ADJUSTABLE LED FOR PRECISE AIMING (120 DEGREE)
- IDEAL FOR COLUMNS, RETAINING WALLS & BENCHES
- FIELD REPLACEABLE LED
- HEAVY DUTY REMOVEABLE STAINLESS STEEL MASONRY BRACKET
- CAN BE USED WITHOUT BRACKET
- DOT FREE ILLUMINATION

PRODUCT SPECIFICATION

MATERIAL	ALUMINUM
LENS	FROSTED ACRYLIC
FINISH	BRONZE
WATTAGE	2.4W
LUMENS	150
VOLTAGE	11-13V AC/DC
LIGHT SPREAD	6-8 FT AVG
LEAD WIRE	71" SPT-2
DIMMABLE	YES*
ROTATION	120°

STEP 1

FIXTURE CONFIGURATION

LED-ML-13-ADJ



KELVIN TEMPERATURE

27K 2700K

30K 3000K



COMPLETE UNIT
MASONRY BRACKET INCLUDED

MODULE UNIT
CAN BE INSTALLED WITHOUT
BRACKET

*PRIMARY SIDE DIMMING: Requires LED magnetic low voltage (MLV) or LED electronic low voltage (ELV) dimmable transformer and compatible LED dimmer (MLV OR ELV) For more information see installation guidelines
+ Fully tested with Lutron Diva (DVLV-600P) dimmer and Lightcraft dimmable transformers

*LOW VOLTAGE SIDE DIMMING: Requires Lightcraft 12V In Line Dimmer

+ Lumens calculated at 3000K
(-5% for 2700K)