



PROJECT	DATE
TYPE	CATALOG #

INVERTED BOLLARD

PATH LIGHT

AP-318B

KEY FEATURES

- **·SOLID BRASS**
- **•CONTEMPORARY DESIGN**
- •NATURAL BRONZE OR BLACK FINISH GUARANTEED NOT TO CHIP, FLAKE OR PEEL
- TEMPERED, SHOCK AND HEAT RESISTENT LENS
- ·HIGH TEMPERATURE CERAMIC SOCKET
- •FIELD REPLACEABLE LED LAMP (NOT INCLUDED)
- ·LIFETIME WARRANTY ON BRASS MATERIAL
- ·HEAVY DUTY 12" STAKE INCLUDED

PRODUCT SPECIFICATION

MATERIAL **SOLID BRASS**

FINISH NATURAL BRONZE OR BLACK

LENS **FROST** SOCKET **BI-PIN**

LAMP T3/G4 OR MR8

12V **VOLTAGE** LIGHT SPREAD 3 FT AVG

STEP 1

FIXTURE CONFIGURATION

AP-318B

FINISH OPTION -

NBZ NATURAL BRONZE

BK BLACK

STEP 3

ACCESSORY OPTIONS

AX-801P INCLUDED

STAKE OPTION —

AX-802P HEAVY DUTY PERMA POST

STEP 2

LED LAMP CONFIGURATION

SPECIFYING YOUR LED

For soft light spread specify **SOFT LED** (73) and for projected light illumination specify **DIRECT PROJECTED LED (MR8)**

LED-T3



LED WATTAGE

1.5W 110 LM 2.5W 210 LM

3.5W 280 LM

5W 400 LM 6W 480 LM

KELVIN TEMPERATURE

27K 2700K 30K 3000K LED-MR8

LED WATTAGE

KELVIN TEMPERATURE

27K 2700K

2.5W 125 LM

30K 3000K