



Project: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Cat.No: \_\_\_\_\_  
 Type: \_\_\_\_\_  
 Lamps: \_\_\_\_\_ Qty: \_\_\_\_\_  
 Notes: \_\_\_\_\_

### Ordering guide

Catalog No.	Finish
9030N PAR30 gimbal ring	<b>WH</b> Matte White <b>BK</b> Matte Black <b>AL</b> Aluminum

**Lamping: 75W PAR30 maximum. Order separately.**

**Track: Mounting compatible with all Philips Lytespan Track Systems.**

### Descriptions

Minimal form specifically designed to create close fit with LED lamps, with cleanly miniaturized detailed yoke and ring-shaped lampholder. Front re-lamping for easy maintenance. Unit adjusts horizontally up to 350°, vertically up to 90°.

### Features

- 1 Lytespan attachment fitting:** molded polycarbonate integral color fitter twists onto track and locks on.
- 2 Push tab:** molded polycarbonate, detaches unit
- 3 Yoke:** 3/4" x .05" steel
- 4 Tension spring washer**
- 5 Ring and socket cup:** molded polycarbonate
- 6 Moveable brass contact:** extends connection to 2nd circuit in Advent Lytespan Track
- 7 Polarity Keyway**

**8 Pivot Mounting:** tensioned 350° stop

### Finish

Black and white finished in molded PBT. Aluminum finish in wet paint.

### Material

PBT material to allow scratch free finish, more precise sizing to fit lamps, and miniaturized design.

### Electrical

Porcelain socket, medium base, nickel-plated screw shell, no. 18 braided SF-1 leads with silicon sleeving.

### Labels

cULus

### Leadtime

All items are spec or service smart.

