



Catalog #: _____ Project: _____

Prepared By: _____ Date: _____ Type: _____

EXC

Cast Aluminum Exit



damp location



FEATURES & SPECIFICATIONS

Construction

- Heavy duty cast aluminum housing with powdercoat finish
- All configurations include field-selectable directional chevrons
- Universal design includes two faceplates, one backplate, and mounting canopy
- Standard finish: White, Black, and Brushed Aluminum
- Buy American Act (BAA) compliant with US option

Optical System

- Illuminated by long-life, high intensity red or green LEDs
- Fully-illuminated 6" characters with 3/4" stroke

Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Solid-state transfer detects loss of line voltage and automatically switches to emergency mode
- Low voltage disconnect eliminates deep discharge
- Test button to provide manual verification of the transfer circuit and emergency lamps

Battery

- Maintenance free NiCad Battery (WB only)
- Operating Temperatures 0°C to 40°C (32°F to 104°F)

Installation

- Includes mounting canopy for wall, ceiling, and end mount applications
- Universal J-box mounting pattern

Warranty

- 5 year warranty on all electronics and housing
- Separate 5 year pro-rated warranty on the battery

Listings

- UL 924
- NFPA 701
- NEC
- CEC
- Damp Location Rated
- UL Listed 90 minute emergency run time, 24 hour recharge time

ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **EXC R U LB BL**

Prefix	Letter Color	# of Faces	Battery	Housing Color	Options
EXC - Cast Aluminum Exit	R- Red G - Green	U - Universal (includes two face plates, back plate, and mounting canopy)	LB - Less Battery (AC Only) WB - With Battery	BL - Black w/ Aluminum Face BB - Black w/ Black Face WW - White w/ White Face WH - White w/ Aluminum Face BA - Brushed Aluminum w/ Aluminum Face	SD21 - Self Test / Self Diagnostic 2C1 - Two Circuit Input US - Meets Buy American Requirements (BAA) WGB1 - Wire Guard Back Mount WGE2 - Wire Guard End Mount WGC3 - Wire Guard Ceiling Mount PGB1 - Polycarbonate Guard Back Mount

FOOTNOTES:
1 - SD2 not available with LB option.

PRODUCT DIMENSIONS

