



Catalog # : _____ Project : _____

Prepared By : _____ Date : _____

CEL

Compact Emergency Light



FEATURES & SPECIFICATIONS

Construction

- Injection-molded UL 94V-0A flame retardant, thermoplastic housing
- Standard finish: White and Black

Optical

- 2W option provides 150 lumens
- 4W option provides 250 lumens

Electrical

- Standard Universal Voltage - 120/277VAC dual primary at 60Hz
- Test button to provide manual verification of the transfer circuit and emergency lamps
- RC option compatible with CRL remote heads

Battery

- Maintenance free NiCad Battery with 2W option
- Maintenance free NiMH Battery with 4W option
- Operating Temperature 0°C to 40°C (32°F to 104°F)
- RC option only available with Ni-MH Battery

Installation

- Universal J-box mounting pattern with keyhole slots

Warranty

- 5 year warranty on all electronics and housing.
- Separate 3 year pro-rated warranty on the battery.

Listings

- UL 924
- cUL
- NFPA 101
- NEC
- 90 minute emergency run time, 24 - 48 hour recharge time
- Suitable for Damp Locations

ORDERING GUIDE

TYPICAL ORDER EXAMPLE: **CEL 4W WH SD2**

Prefix	Output	Housing Color	Options
CEL - Compact Emergency Light	2W ¹ - 2 Watts Total 4W ² - 4 Watts Total	WH - White BK - Black	SD2 ³ - Self Test/Self Diagnostic RC ⁴ - 2W Remote Capacity WGB1 - Wire Guard Back Mount PGB1 - Polycarbonate Guard Back Mount

1 - 2W option comes with NiCad battery
 2 - 4W option comes with NiMH battery
 3 - SD2 option not available with CEL 2W BK
 4 - RC option not available with 2W selection

PRODUCT DIMENSIONS

