


INDUSTRIAL COMPARISON

GUIDE

TABLE OF CONTENTS

| OUR STORY Industry Experience |
|--|
| YOUR INDUSTRIAL FACILITY Illustrated View of Products & Solutions |
| HIGH BAY PRODUCT COMPARISON Linear & Round High Bay Fixtures |
| ENCLOSED & GASKETED PRODUCT COMPARISON Linear Fixtures for Special Applications |
| STRIP LIGHTING PRODUCT COMPARISON LED Industrial Linear Fixtures |



INTRODUCTION

Warehouses, manufacturing plants, distribution centers, and other industrial spaces are the hidden infrastructure that keep society moving forward. The food at your local grocery store, that order from your favorite e-commerce site, it all comes from a warehouse. The "cloud" where you store all your important files, pictures, or music isn't a cloud at all, but a warehouse, holding massive servers and other high-tech equipment that make our modern lives possible.

If these facilities are the backbone of our economy, they require the very best people and equipment to operate at their peak. When it comes to meeting shipping and delivery deadlines, all the details matter.

One of the most important details to keep the people and equipment productive, and the products moving in these industrial spaces, is reliable, quality lighting throughout the facility.

LSI delivers the most versatile lineup of industrial lighting solutions in the business. Manufactured in the U.S. and designed to enhance safety and increase productivity, our lighting solutions will also reduce energy costs.

Add to that our custom configuration and wireless control options for the ultimate in streamlined, low maintenence lighting solutions.







HIGH BAY









STRIPS



ENCLOSED & GASKETED











High Bay Position Guide

Linear & Round High Bay Fixtures for EVERY Application

- Energy efficient, easy contractor-friendly lighting solutions
- · Lightweight designs allow for minimal installation effort
- Form factor and lumen packages for every opportunity





High Bay Position Guide



| | Industrial Linear High Bay (IHB) | Advantage High Bay LED (AHB) | Modular High Bay Light (MHB) | Alliance High Bay (ALI) | Round High Bay LED (RHB) | Aureus LED Round High Bay (AUL) |
|--------------------|--|---|---|---|---|--|
| | *** | *** | *** | **** | *** | **** |
| Applications | Warehouse, Manufacturing, Service Bays, Retail | Warehouse, Manufacturing, Service Bays, Retail, Gymnasium | Warehouse, Manufacturing, Service Bays, Retail, Gymnasium | Warehouse, Manufacturing, Service Bays, Retail, Gymnasium | Light Duty, Warehouse, Manufacturing, Retail, Gymnasiums | Light Duty, Warehouse, Manufacturing, Retail, Gymnasiums, |
| Colors Available | White | White | White | White | White, Black | White, Black, Silver, Custom |
| Sizes Available | 2', 4' | 2', 4' | 1', 2', 3' length | 2', 4' | 13.5" Diameter | 15" Diameter |
| Mounting Height | Up to 40' | Up to 60' | Up to 60' | Up to 90' | Up to 40' | Up to 40' |
| Delivered Lumens | 9,000 to 30,000 | 18,000 to 60,000 | 12,000L - 90,000L | 12,000 to 100,000 | 18,000 to 30,000 | 6,000 to 30,000 |
| ccτ | 4000K, 5000K | 4000K, 5000K | 4000K, 5000K | 4000K, 5000K | 4000K, 5000K | 3000K, 3500K, 4000K, 5000K |
| LPW | Up to 154 LPW | Up to 138 LPW | Up to 162 LPW | Up to 172 LPW | Up to 133 LPW | Up to 162 LPW |
| Temperature Rating | Up to 55C | Up to 50C | Up to 50C | Up to 60C | 50C | 50C |
| Listings | Damp Location | Damp Location | Damp Location | Damp Location | Wet Location, IP65 | Damp Location |
| DLC ¹ | Premium | Premium | Standard | Premium | Premium | Premium |
| Optics Options | No Lens, Acrylic (Diffuse) | Acrylic (Frosted) | Polycarbonate (Clear, Diffuse) | No Lens, Acrylic (Clear, Diffuse) | Open w/Refractor (16" or 22") | Open w/Refractor (16" or 22") |
| Distributions | Wide (120) | Wide (120) | Wide (120), Narrow (30) | Wide (120), Narrow (30) | General | General |
| Voltage Range | 120V - 480V | 120V - 277V | 120V - 480V | 120V - 480V | 120V - 480V | 120V - 480V |
| Battery Backup | Yes | Yes | Yes | Yes | Yes | Yes |
| Controls/Sensors | External PIR Motion Sensor External PIR Motion Sensor Bluetooth | External PIR Motion Sensor Integral/External PIR Motion Sensor Bluetooth | External PIR Motion Sensor Integral/External PIR Motion Sensor Bluetooth | AirLink Synapse Indoor External PIR Motion Sensor Integral/External PIR Motion Sensor Bluetooth | External PIR Motion Sensor | AirLink Synapse Indoor Integral PIR Motion Sensor Bluetooth |
| Pricing | \$ | \$ | \$\$ | \$\$\$ | \$\$ | \$\$\$ |

1 Not all versions of this product may be qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.





Enclosed and Gasketed Position Guide

Linear Fixtures for Special Applications

- Energy efficient, easy contractor-friendly lighting solutions
- IP65/IP66/IP67 and NSF ratings for specialty applications
- Variety of lens colors and textures available for every application





Enclosed and Gasketed Position Guide



| | Enclosed and Gasketed – Advantage Series (EGA) | Enclosed and Gasketed Linear LED Fixture (EG3) | Enclosed and Gasketed Linear LED Fixture – Wide Wet Location (EGW) | |
|-------------------|---|---|--|--|
| | *** | *** | *** | |
| Applications | Warehouse, Manufacturing, Strvice Bays, Retail Cold Storage | Warehouse, Manufacturing, Service Bays, Retail Cold Storage | Warehouse, Manufacturing, Service Bays, Retail Cold Storage | |
| izes Available | 4' | 2', 4', and 8' | 4' and 8' | |
| uminaire Width | 43/8" | 63/4" | 14 1/2" | |
| Nounting Height | Up to 12' | Up to 16' | Up to 30' | |
| elivered Lumens | 5,000L | 4,000L - 13,000L | 10,000L - 27,000L | |
| ст | 4000K, 5000K | 3500K, 4000K, 5000K | 4000K, 5000K | |
| /attage | 36 | 32 - 95 | 69 - 190 | |
| PW | Up to 138 LPW | Up to 143 LPW | Up to 147 LPW | |
| emperature Rating | Up to 40C | Up to 40C | Up to 40C | |
| stings | Wet Location, IP65 | Wet Location, IP65/IP66/IP67, NSF (Zone 2) | Wet Location, IP65/IP66/IP67, NSF (Zone 2) | |
| נני | Premium | Premium | Premium | |
| ens Colors | Diffuse | Clear, Diffuse | Clear, Diffuse | |
| ens Types | Ribbed | Smooth ² , Ribbed | Smooth, Ribbed | |
| oltage Range | 120V - 277V | 120V - 480V | 120V - 480V | |
| attery Backup | No | Yes | Yes | |
| ontrols/Sensors | None | External PIR Motion Sensor (OCSWL) | External PIR Motion Sensor (OCSWL) | |
| ricing | Ş | SS | sss | |

1 Not all versions of this product may be qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified 2 Not all versions of this product may be are available with this lens type





Strip Lighting Position Guide

END VIEW







LED Industrial Linear Fixtures

• Energy efficient, easy contractor-friendly lighting solutions

AST 4' and 8' UP TO 8,000L

S 2', 4' and 8' UP TO 18,000L

SDL 2', 4' and 8' UP TO 18,000L



INDIVIDUAL



STORAGE INDUSTRIAL AREA SHOP FLOOR



INDIVIDUAL OR CONTINUOUS



STORAGE INDUSTRIAL AREA SHOP FLOOR / AUTO SERVICE AREA







INDIVIDUAL OR CONTINUOUS



STORAGE / HOSPITALITY RETAIL / AUTO SERVICE AREA



SHOP FLOOR

Strip Lighting Position Guide



| | Advantage Series LED Strip Fixture (AST) | Indoor Industrial LED Strip Light (S) | Diffused Lens Strip (SDL) | |
|--------------------|---|---|---|--|
| | *** | *** | **** | |
| Applications | Warehouse, Manufacturing, Service Bays, Retail, Utility and Storage Areas | Warehouse, Manufacturing, Service Bays, Retail, Utility and Storage Areas | Warehouse, Manufacturing, Service Bays, Retail, Utility and Storage Areas | |
| Sizes Available | 4' and 8' | 2', 4', and 8' | 2', 4', and 8' | |
| Luminaire Width | 4 3/8" | 4 3/8" | 33/8" | |
| Mounting Height | Up to 12' | Up to 20' | Up to 20' | |
| Mounting | Surface, Chain/Cable (sold separately) | Surface, Chain/Cable/Pendant (sold separately) | Surface, Chain/Cable/Pendant (sold separately) | |
| Delivered Lumens | 4,000L - 8,000L | 1,500L - 18,000L | 1,500L - 18,000L | |
| ατ | 3500K, 4000K, 5000K | 3000K, 3500K, 4000K, 5000K | 3000K, 3500K, 4000K, 5000K | |
| Wattage | 20 - 65 | 12 - 142 | 12 - 142 | |
| LPW | Up to 133 LPW | Up to 159 LPW | Up to 147 LPW | |
| Temperature Rating | Up to 50C | Up to 50C | Up to 50C | |
| Listings | Damp Location | Damp Location | Damp Location | |
| DLC¹ | Premium | Premium | Premium | |
| Lens | Diffuse Rounded | No Lens | Diffuse Rounded | |
| Voltage Range | 120V - 277V | 120V - 480V | 120V - 480V | |
| Battery Backup | Yes | Yes | Yes | |
| Retrofit Kits³ | No | Yes | Yes | |
| Controls/Sensors | No | External PIR Motion Sensor (OMSx) AirLink Blue Controller (ALBC) AirLink Blue Controller & Sensor (ALBCS) | External PIR Motion Sensor (OMSx) AirLink Blue Controller (ALBC) AirLink Blue Controller & Sensor (ALBCS) | |
| Pricing | \$ | \$\$ | ss | |

1 Not all versions of this product may be qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified 2 Not all versions of this product may be are available with this lens type



Visit us online or contact your account manager for more information.

LSIcorp.com | (800) 436-7800



