Lumark AP
CLCS Canopy
Features and Benefits

The CLCS canopy luminaire provides a slim, low-profile, traditional design with high performance energy efficient illumination. Rugged die-cast aluminum construction and gasketed housing make the CLCS luminaire virtually impenetrable to contaminants. Replacing up to 400W metal halide equivalents, the CLCS canopy luminaire mounts quickly to a variety of surfaces making it ideal for bank and retail drive-thrus, covered side walks and hospitality entryways.

CLCS Small

CLCS Large

PRODUCT FEATURES

- Fixed output and selectable configurations available
- Replaces 150W up to 400W HID equivalent
- Efficacies up to 153 lumens per watt at maximum output
- Energy and maintenance savings up to 86% versus HID solutions

DESIGN FEATURES

Selectable lumens and CCT
Integrated switches to field-select high or low lumen output and choose between 3000, 4000, and 5000K CCTs

Drop Lens
Refractive, polycarbonate lens distributes light to maximize area coverage and provide visual glow for a preferred safety aesthetic

Mounting
Direct mount to junction box or 1/2" NPT pendant

Installation
Quick mount plate and tether provide fast and easy wiring and installation

QUICK FACTS

- Lumen packages ranging from 5,500 - 17,600 lumens
- 2 housing sizes
- > 134,000 hour lifetime

ISO SYSTEMS CERTIFIED · DLC QPL LISTED · FC CLASS A CAN ICES-005 · IP65

UL CERTIFIED SAFETY · RoHS COMPLIANT · 5 YEAR LIMITED WARRANTY

seleCCTable colors · Selectable lumens

COOPER
Lighting Solutions

Lumark AP
CLCS Canopy
Features and Benefits

Stock Ordering Information

Catalog Number	HID Equivalent	Lumens	Input Watts	Color Temperature	Controls	Pallet Quantity	UPC Code
CLCS15	150W	5,500	40W	4000K / 80CRI	--	72	080083161003
CLCS17	175W	8,000	60W	4000K / 80CRI	--	72	080083161041
CLCS17S	150 - 175W	Selectable Lumens: 5,000 - 8,000	40-60W	Selectable CCT: 3000, 4000, 5000K / 80CRI	--	72	080083160006
CLCS17S-PC	150 - 175W	Selectable Lumens: 5,000 - 8,000	40-60W	Selectable CCT: 3000, 4000, 5000K / 80CRI	Button-type photocontrol	72	080083159727
CLCS40S	250 - 400W	Selectable Lumens: 13,600 - 17,600	90-120W	Selectable CCT: 3000, 4000, 5000K / 80CRI	--	36	080083160020