

# Lumark

## RPGC Round Parking Garage and Canopy Features and Benefits

### Energy-efficient optical control

The Lumark RPGC Round Parking Garage and Canopy luminaire is an innovative, energy-efficient LED fixture. The RPGC is designed to replace traditional HID fixtures on a one-to-one basis from 150W up to 250W HID. The low profile, rugged construction, features a selectable lumen switch that allows for seamless integration into illuminating parking garages, canopy, stairwells and low-bay retail installations where high security illumination and energy savings are needed.

### PRODUCT FEATURES

- Heavy-duty, die-cast aluminum housing provides durability and reliability
- Round drop lens with refractive features distributes light to maximize area coverage and provides uplight to eliminate dark ceilings
- Mounts directly to junction box or pendant to allow for versatility in installation
- Maintains greater than 90% of initial light output after 50,000 hours of operation

### DESIGN FEATURES



#### Selectable lumen switch

Field-adjustable lumen output switch accessible via 1/2" NPS plug



#### Sensor

Factory-installed motion sensor maximizes energy savings and code compliance



#### Mounting

Easy installation with quick-mount bracket system for hands-free wiring



### QUICK FACTS

- Lumen selectable from 3,700 up to 7,800 lumens
- 120 - 277V or 347V
- 4000K CCT; 70 CRI
- IP65 rated, UL/cUL Wet Location Listed
- Operates at -40°C to 40°C

# Lumark

## RPGC Round Parking Garage and Canopy

### Features and Benefits

#### STOCK ORDERING INFORMATION

Catalog Number	HID Equivalent	Description	Input Watts	Lumens	Efficacy (LPW)	UPC
<b>RPGC25S</b>	150 - 250W	Lumen Selectable, UNV	30 - 60W	3,700 - 7,800	119 - 125	080083885664
<b>RPGC25S-347</b>	150 - 250W	Lumen Selectable, 347V	30 - 60W	3,700 - 7,800	119 - 125	080083885688
<b>RPGC25-MS/DIM-L08</b>	150 - 250W	Motion Sensor, Up to 8' Mounting Height, UNV	30 - 60W	3,700 - 7,800	119 - 125	080083885701
<b>RPGC25-MS/DIM-L20</b>	150 - 250W	Motion Sensor, 9 - 20' Mounting Height, UNV	30 - 60W	3,700 - 7,800	119 - 125	080083885725
<b>RPGC25-347-MS/DIM-L08</b>	150 - 250W	Motion Sensor, Up to 8' Mounting Height, 347V	30 - 60W	3,700 - 7,800	119 - 125	080083911844
<b>RPGC25-347-MS/DIM-L20</b>	150 - 250W	Motion Sensor, 9' - 20' Mounting Height, 347V	30 - 60W	3,700 - 7,800	119 - 125	080083911868



**Eaton**  
1121 Highway 74 South  
Peachtree City, GA 30269  
P: 770-486-4800  
[www.eaton.com/lighting](http://www.eaton.com/lighting)

**Canada Sales**  
5925 McLaughlin Road  
Mississauga, Ontario L5R 1B8  
P: 905-501-3000  
F: 905-501-3172

© 2019 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. SA00029EN  
November 14, 2019 8:20 AM

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Product availability, specifications, and compliances are subject to change without notice.