



POLE CAT. NO.	SHAFT SIZE
	A
405-8015-25	8.00 DIA.
405-8015-27	8.00 DIA.
405-8018-27	8.00 DIA.
405-8015-30	8.00 DIA.
405-8018-30	8.00 DIA.
405-8025-30	8.00 DIA.
405-8018-35	8.00 DIA.
405-8025-35	8.00 DIA.
405-8018-39	8.00 DIA.
405-8025-39	8.00 DIA.

**WARNING:** THE FACTORY WILL NOT HONOR ANY CLAIM FOR INCORRECT ANCHORAGE PLACEMENT CAUSED FROM FAILURE TO USE FULL SIZE, FACTORY SUPPLIED TEMPLATES. IT IS POSSIBLE FOR DOWNLOADED FILES TO BE DISTORTED WHEN PRINTING FROM WEBSITE. IT IS THE CONTRACTORS RESPONSIBILITY TO VERIFY ACCURATE MEASUREMENTS.

**NOTE:** BOLT PROJECTION RANGE ABOVE FOUNDATION 3.50 MIN.-4.00 MAX WHEN LEVELING NUTS AND GROUT ARE USED.

**SET ANCHOR BOLTS AT Ø11.50 BOLT CIRCLE.**

DRAWN: M. HARVALA	DATE: 4-2-09	LYTE POLES, INC. P.O. BOX 340 EASTPOINTE, MI 48021	
CHECKED:		TITLE: T-8A Ø11.00-Ø12.00	
QA:		SIZE: D	DWG NO: T-8A
MFG:		SCALE:	REV: A
APPROVED:		SHEET: 1 OF 1	