

COOPER LIGHTING SOLUTIONS - METALUX®

DESCRIPTION

The GR8IC is a T8-dedicated lensed troffer designed to offer premium performance in a low profile housing. T8 dedication and optimized lamp to lens spacing provides the best in energy efficiency and optical control. The GR8IC is designed for installations when the housing will be in direct contact with installation.

The GR8IC offers great performance and great quality. The series is an excellent choice for commercial offices, schools, hospitals, retail merchandising and many other applications.

Catalog #		Type
Project		
Comments		Date
Prepared by		

SPECIFICATION FEATURES

Construction

Unitized low profile recessed housing is die formed of code gauge prime cold rolled steel with full length stiffeners and unibody endplate for added strength. Ballast cover is easily removed without tools. Die formed captive lampholder bracket fully encloses lampholder wiring for easy lampholder replacement. Ample KO's are provided for continuous row wiring. Built-in grid-lock feature for safety and convenience.

Electrical**

Ballasts are CBM/ETL Class "P" and are positively secured by mounting bolts. Rotor-lock lampholders. UL/cUL Listed Type IC Recessed Luminaire for direct contact with insulation. Suitable for damp locations.

Finish

Multistage, iron phosphate pretreatment ensures maximum bonding and rust inhibition. Lighting grade baked white enamel finish with premium reflectance for high efficiency.

Hinging/Latching

Positive spring loaded steel latches and safety lock T-hinges provide secure, high quality door fit and allow hinging and latching from either side.

Frame/Shielding

Heavy gauge flat steel door is die formed with reinforced mitered corners. Housing and door frame assemblies incorporate full width mechanical light traps. Light stabilized, acrylic prismatic lens.

Controls

Fifth Light ballast options are offered for both 0-10V continuous dimming and DALI applications. Combine with energy-saving products like occupancy sensors, daylighting controls, and lighting relay panels from Cooper Lighting Solutions (www.cooperlighting.com) to maximize energy savings.



2GR8IC
2U6T8
2U1-5/8
217, 317, 417

2' X 2' TROFFER
2, 3 OR 4 LAMPS

General Purpose
 T8 Commercial Troffer

**FOR USE IN INSULATED
 CEILINGS**



ENERGY DATA

Input Watts:
EB Ballast & STD Lamps
 217 (36), 2U1-5/8 (61), 2U6T8 (61)
 317 (52), 417 (63)

Luminaire Efficacy Rating
LER = FL-73
Catalog Number: 2GR8IC-2U6T8A

**Yearly Cost of 1000 lumens, 3000
 hrs at .08 KWH = \$3.29**

*Standard G (Grid) Type Fixtures can be field converted by adding trim kits. See Compatibility Section or Consult Factory.

**Reference the lamp/ballast data in the Technical Section for specific lamp/ballast requirements.

***Order FCS-22W-U Flange Kit for installation in drywall ceiling. See options and accessories compatibility section.


**LAMPS CONTAIN MERCURY. DISPOSE ACCORDING TO LOCAL,
 STATE OR FEDERAL LAWS**

LINEAR DISCONNECT


Safe and convenient means of
 disconnecting power.



ADF100878




MOUNTING DATA




DOOR FRAMES


2GR8
 Flat, White
 Steel (White
 Latches)



LAMP CONFIGURATIONS




CEILING COMPATIBILITY



Ceiling Type	Trim Type
Exposed Grid	G
Concealed T	G
Slot Grid	G
Flange	G***


COOPER LIGHTING SOLUTIONS

PHOTOMETRICS



2GR81C-2U6T8A
 Electronic Ballast
 (2) 31W U6T8 lamps
 2850 lumens
 Spacing criterion:
 (H) 1.2 x mounting
 height, (L) 1.3 x
 mounting height
 Efficiency 77.1%
 Test Report:
 2GR81C-2U6T8A.IES
 LER = FL-73
 Yearly Cost of 1000
 lumens, 3000 hrs at
 .08 KWH = \$3.29

Candela			
Angle	Along H	45°	Across L
0	1775	1775	1775
5	1771	1769	1773
10	1742	1749	1768
15	1696	1717	1749
20	1629	1672	1719
25	1547	1607	1670
30	1443	1522	1591
35	1317	1406	1486
40	1171	1264	1363
45	996	1075	1195
50	805	877	993
55	638	688	780
60	491	495	574
65	361	330	406
70	271	224	307
75	210	175	245
80	153	146	179
85	82	86	90
90	0	0	0



2GR81C-217A
 Electronic Ballast
 (2) F32T8 lamps
 1350 lumens
 Spacing criterion:
 (H) 1.2 x mounting
 height, (L) 1.4 x
 mounting height
 Efficiency 75.1%
 Test Report:
 2GR81C-217A.IES
 LER = FL-60
 Yearly Cost of 1000
 lumens, 3000 hrs at
 .08 KWH = \$4.00

Candela			
Angle	Along H	45°	Across L
0	795	795	795
5	794	792	796
10	782	785	794
15	763	774	790
20	734	756	781
25	699	731	765
30	652	697	734
35	597	648	695
40	528	586	646
45	449	503	574
50	363	413	478
55	287	325	371
60	220	235	273
65	165	155	189
70	123	104	143
75	96	81	112
80	70	68	82
85	38	39	40
90	0	0	0

Coefficients of Utilization

rc	Effective floor cavity reflectance																							
	80%				70%				50%				30%				10%				0%			
	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
0	92	92	92	92	90	90	90	90	86	86	86	82	82	82	79	79	79	77						
1	84	81	78	75	82	79	77	74	76	74	72	73	71	69	70	69	67	66						
2	77	72	67	63	75	70	66	62	67	64	60	65	62	59	63	60	58	56						
3	71	63	58	53	69	62	57	52	60	55	51	58	54	51	56	53	50	48						
4	65	57	50	45	64	56	50	45	54	49	45	52	48	44	50	47	43	42						
5	60	51	44	40	59	50	44	39	49	43	39	47	42	39	46	41	38	37						
6	56	46	40	35	55	45	39	35	44	39	34	43	38	34	42	37	34	32						
7	52	42	36	31	51	41	35	31	40	35	31	39	34	30	38	34	30	29						
8	49	38	32	28	47	38	32	28	37	31	28	36	31	27	35	31	27	26						
9	45	35	29	25	44	35	29	25	34	29	25	33	28	25	32	28	25	23						
10	43	33	27	23	42	32	27	23	32	26	23	31	26	23	30	26	22	21						

Coefficients of Utilization

rc	Effective floor cavity reflectance																							
	80%				70%				50%				30%				10%				0%			
	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
0	89	89	89	89	87	87	87	87	83	83	83	80	80	80	77	77	77	75						
1	82	79	76	73	80	77	74	72	74	72	70	71	69	68	68	67	66	64						
2	75	70	65	61	73	68	64	60	66	62	59	63	60	57	61	58	56	54						
3	69	62	56	51	67	61	55	51	58	54	50	56	52	49	54	51	48	47						
4	64	55	49	44	62	54	48	44	52	47	43	51	46	43	49	45	42	40						
5	59	49	43	38	57	49	43	38	47	42	38	46	41	37	44	40	37	35						
6	54	45	38	34	53	44	38	34	43	37	33	41	37	33	40	36	33	31						
7	50	41	34	30	49	40	34	30	39	34	30	38	33	29	37	33	29	28						
8	47	37	31	27	46	37	31	27	36	30	27	35	30	26	34	30	26	25						
9	44	34	28	24	43	34	28	24	33	28	24	32	27	24	31	27	24	22						
10	41	32	26	22	40	31	26	22	30	25	22	30	25	22	29	25	22	20						

Zonal Lumen Summary

Zone	Lumens	%Lamp	%Fixture
0-30	1394	24.5	31.7
0-40	2269	39.8	51.6
0-60	3729	65.4	84.8
0-90	4398	77.1	100.0
0-180	4398	77.1	100.0

Luminance Data

Angle in Deg	Average 0-Deg cd/sm	Average 45-Deg cd/sm	Average 90-Deg cd/sm
45	3789	4090	4546
55	2992	3227	3658
65	2298	2100	2584
75	2183	1819	2546
85	2531	2654	2778

Zonal Lumen Summary


Zone	Lumens	%Lamp	%Fixture
0-30	631	23.4	31.1
0-40	1035	38.3	51.0
0-60	1718	63.6	84.7
0-90	2027	75.1	100.0
0-180	2027	75.1	100.0

Luminance Data

Angle in Deg	Average 0-Deg cd/sm	Average 45-Deg cd/sm	Average 90-Deg cd/sm
45	2231	2499	2852
55	1758	1991	2273
65	1372	1289	1571
75	1303	1100	1520
85	1532	1572	1613

ORDERING INFORMATION

SAMPLE NUMBER: 2GR81C-2U6T8A-UNV-EB81-U




NOTES: ⁽¹⁾An EQ Grid Clip is recommended for all 9/16" ceiling systems. Four required per fixture. ⁽²⁾Products also available in non-US voltages and frequencies for international markets. ⁽³⁾Not available when specifying emergencies, voltage must be specific. ⁽⁴⁾Standard off center ballast on 3 lamp fixtures. ⁽⁵⁾2 lamps maximum for U6T8 and U1-5/8. ⁽⁶⁾Ballast Factor is 0.88 for 4 lamp 32W T8 fixtures. ⁽⁷⁾Fifthlight ballast option not available. ⁽⁸⁾For a complete listing of Fifthlight Technology products and other solutions from Cooper Lighting Solutions, visit www.cooperlighting.com. ⁽⁹⁾0-10V ballast do not include DALI feature. Please select DALI ballast for use with Fifth Light system. ⁽¹⁰⁾Specification grade 0-10V dimming ballast are NEMA premium and CEE listed. They are compatible with low mercury and energy saving lamps. ⁽¹¹⁾Specification Grade 0-10V ballast not offered in 3 or 4-lamp versions. ⁽¹²⁾Standard 0-10V ballast not offered in 3 or 4-lamp versions. ⁽¹³⁾Please specify required voltage, 120V or 277V.

For complete product data, reference the Fluorescent Specification binder. Specifications & dimensions subject to change without notice. Consult your Cooper Lighting Solutions Representative for availability and ordering information.

ACCESSORIES

EQ-CLIP-U=T-BAR Safety Earthquake Clips⁽¹⁾
FCTKA-22W-U=Field Installed Flange Kit



SHIPPING INFORMATION

Catalog No.	Wt.
2GR81C-217A	12 lbs.
2GR81C-417A	12 lbs.
2GR81C-2U6T8A	12 lbs.
2GR81C-2U1-5/8A	12 lbs.