	Good —				Better					Best =	
	n products arn more										
		SLES ²	ST	ST DIM	SLSTP	SSRK Retrofit	SNLED	SRL	SWLED	WSL	
	Education	*	**	**	***	*	***	***	***	**	
APPLICABILITY1	Office	*	**	**	***	*	***	***	***	***	
	Healthcare				*	*	**	**	*	**	
	Retail	***	*	**	**	***	***	***	*	***	
	Industrial	**	**	**	**	***	***	***	**	**	
	Residential		***		**						
	Length	4', 8'	2', 4', 8'	2', 4', 8'	2', 4', 8'	4', 8'	2', 4', 8'	4', 8'	4'	4', 8'	
FEATURES / PERFORMANCE	Im/W (Max)	167 (8ft)	108	115	125	159	150	149	150	121	
	Lum (Max)	8,700	9,200	9,200	10,500	8,000 / 4 ft.	17,000	11,000	8,000	16,000	
	Life (@60K)	L70/50K ³	L70/50K	L70/50K	L70/50K	L94	L87	L82	L91	L81	
	Dimming	N/A	No	0-10V	Triac or 0-10V	0-10V	0-10V, Step, Dali	0-10V, Step, Dali	0-10V, Step, Dali	0-10V, Step, Dali	
S / PEF	Lens	None ⁴	White, Single or Dual Lens	White, Dual Lens	Clear, Poly	Frost, Acrylic	Frost, Acrylic	Frost, Acrylic	(Vandal Resistant) Frost, Acrylic	WaveStream, Acrylic	
FEATURES	Emergency	Integrated	None	None	None	Integrated	Integrated	Integrated	Integrated	Integrated	
	CRI	80+	80+	80+	80+	80+	80+	80+	80+	80+	
	Sensor Location	Remote	Remote	Remote	Simple ("CS")	N/A	Integrated	Integrated	Integrated	Integrated	
	DLC	Standard (TLED Lamps only)	Standard	Standard	Standard	Premium	Premium	Premium	Standard	Standard	
INTEGRATED	Basic Occupancy		_		✓	V	✓	✓	✓	✓	
	Stand Alone Daylight / Occupancy					~	~	~	~	~	
	WaveLinx Lite							✓	~	✓	
	WaveLinx							✓	✓	~	
	DLVP									✓	

Notes: 1. *\daggreen \daggreen = high applicability, *\daggreen = medium applicability

