

POWER CONNECTIONS

DESIGNATION

DESCRIPTION


Modular Cord & Plug



- MPC3**=3' Modular Power Cord & Plug (specify voltage for plug)
- MPC6**=6' Modular Power Cord & Plug (specify voltage for plug)
- MPC9**=9' Modular Power Cord & Plug (specify voltage for plug)
- MPC12**=12' Modular Power Cord & Plug (specify voltage for plug)
- MPC15**=15' Modular Power Cord & Plug (specify voltage for plug)

Connect directly to F-Bay or Modular Motion Sensor with a 3', 6', 9', 12' or 15' long modular cord & plug set w/NEMA 15 amp twist lock plug.

Modular Cord



- MC3**=3' Cord
- MC6**=6' Cord
- MC9**=9' Cord
- MC12**=12' Cord
- MC15**=15' Cord

Connect directly to F-Bay or Modular Motion Sensor with a 3', 6', 9', 12' or 15' long 3/16" standard Modular Power Cord.

POWER CONNECTIONS

DESIGNATION

DESCRIPTION

MWS



MWS= Modular Wiring System

MWS is a simple and cost effective modular wiring system consisting of factory assembled components ready to be snapped together into a complete branch circuit wiring system.

With MWS, branch circuit wiring can be installed in minutes instead of hours reducing labor by 80%.

MDS6= 6' Modular Power Cord with MWS 27DS18/2G06MP.

Connect directly to F-Bay or Modular Motion Sensor with a 6' long Cord and MWS Connector.

Items listed are the major options and accessories available on Metalux Recessed (Parabolic and Recessed) and Surface Fixtures. Additional options and accessories are available. Consult Pre Sales Technical Support for additional information.

