

Project		Catalog #		Type	
Prepared by		Notes		Date	



Metalux

LBLED

Low Bay Linear Series
Asymmetric Distribution

Typical Applications

- Industrial • Loading docks • Commercial

Interactive Menu

- Order Information [page 2](#)
- Photometric Data [page 4](#)
- Product Warranty

Product Certification




Product Features



Top Product Features

- Die formed CRS housing painted after fabrication for added durability
- High Impact optical lens protects LEDs
- Available lumen packages up to 22,000 lumens
- High-Performance efficacy up to 154 lm/W
- Asymmetric distribution is ideal for loading docks
- Options to meet Buy American and other domestic preference requirements

Dimensional and Mounting Details



Order Information

SAMPLE ORDER NUMBER: **4LBLED-LD4-8-ASYMF-UNV-L840-CD2-U**

Domestic Preferences	Length	Series	Lamp Type	LED Lumen Output		Optic	Voltage	CCT Options
Domestic Preferences ⁽¹⁾	Length	Series	Lamp Type	LED Lumen Output		Optic	Voltage	CCT Options
[Blank] =Standard BAA =Buy American Act TAA =Trade Agreements Act	4=4' Length 8=8' Length	LBLED =Linear LED Low Bay Series	LD4 =LED 4.0	4 ft. 6=6000 7=7000 8=8000 9=9000 10=10000	8 ft. 9=9000 10=10000 12=12000 14=14000 16=16000	ASYMW =Asymmetric, white ASYMF =Asymmetric, frost	UNV =Universal Voltage 120-277 347V =347 Volt	L835 =3500K L840 =4000K L850 =5000K
<p>Notes</p> <p>(1) Only product configurations with these designated prefixes are built to be compliant with the Buy American Act of 1933 (BAA) or Trade Agreements Act of 1979 (TAA), respectively. Please refer to DOMESTIC PREFERENCES website for more information. Components shipped separately may be separately analyzed under domestic preference requirements.</p>								

Driver Type	Number of Drivers	Wiring	Packaging
Driver Type	Number of Drivers	Wiring	Packaging
CD =0-10V Dimming Driver (10% - 100% Dimming)	2=2 Drivers 3=3 Drivers (8 ft. 347V in 12,000, 14,000, 16,000 lumens)	C3 (1) =1 Circuit, 3' Cord with no Plug C3 (2) =2 Circuits, 3' Cord with no Plug C6 (1) =1 Circuit, 6' Cord with no Plug C6 (2) =2 Circuits, 6' Cord with no Plug PC3/120 =(NEMA L5-15P) 3' Cord with NEMA Plug PC3/277 =(NEMA L7-15P) 3' Cord with NEMA Plug PC3/347 =(NEMA L24-20P) 3' Cord with NEMA Plug PC6/120 =(NEMA L5-15P) 6' Cord with NEMA Plug PC6/277 =(NEMA L7-15P) 6' Cord with NEMA Plug PC6/347 =(NEMA L24-20P) 6' Cord with NEMA Plug	U =Unit Pack

Accessories

Accessories (order separately) ⁽²⁾
AYC-Chain/Set =36" Chain Hanger (Use 1 set per fixture) SCF =Fixed Stem Set (Specify Length) SCS =Swivel Stem Set (Specify Length) SCA =Adjustable 48" Stem Set EYE CHAIN SET/3FT =Eye Bolt Chain (Use 1 set per fixture) A1B/Spacer-U =Spacer 1-1/2" to 2-1/2" from ceiling (Use 2 per fixture) TOGGLE =Single Toggle No. 2 (Specify Length) Y-TOGGLE =Y Toggle No. 2 (Specify Length)
<p>Notes</p> <p>(2) Accessories sold separately will be separately analyzed under domestic preference requirements. Consult factory for further information.</p>

Product Specifications

Construction

- Channel is die formed cold rolled steel
- Available in 4' and 8' lengths
- Groove for Tong Hanger
- Numerous KO's for easy installation
- Channel/wireway cover secured with sheet metal screws

Controls

- Equipped standard with a 0-10V continuous dimming driver that works with any standard 0-10V control/dimmer
- Dimming range is 10% to 100%; varies by control device
- Combine with energysaving products like occupancy sensors, day lighting controls, and lighting relay panels to maximize energy savings
- Motion control can be installed in end K.O. for linear applications

Electrical

- LED's available in 3500K, 4000K, and 5000K with a typical 85 CRI. Other color temperatures are available
- Long-Life LED system coupled with electronic (120-277V) driver to deliver optimal lighting performance
- Projected life is 60,000 hours at 70% lumen output
- 0-10V dimming driver standard

Emergency Battery Pack Option

- Consult factory for battery pack

Finish

- High reflective paint after fabrication, baked white enamel finish is standard
- Multistage cleaning cycle
- Iron phosphate coating with rust inhibitor

Channel/Wireway Cover

- Die formed heavy gauge steel
- Tight fit for ease of maintenance

Shielding

- Offers two different optical distributions and aesthetics - White and Frost

Installation

- Fixture may be surface, pendant, or stem mounted. See accessories in ordering information.

Compliance


- Components are UL recognized
- Indoor luminaires are cULus listed for -20C to 40C ambient environments
- RoHS compliant
- Damp location listed, and comply with IESNA LM-79
- LEDs comply with LM-80 standards

Warranty

- Five year warranty.

Photometric Data

[View IES files](#)



Energy and Performance Data

Energy and Performance Data by Catalog Number

Catalog Number	Delivered Lumens	Watts	Efficacy (lm/W)
Asymmetric			
4LBLED-LD4-6-ASYMF-UNV-L850-CD2-U	6787	46	147
4LBLED-LD4-7-ASYMF-UNV-L850-CD2-U	8043	56	143
4LBLED-LD4-8-ASYMF-UNV-L850-CD2-U	9020	64	141
4LBLED-LD4-9-ASYMF-UNV-L850-CD2-U	10036	73	138
4LBLED-LD4-10-ASYMF-UNV-L850-CD2-U	10991	83	133
8LBLED-LD4-9-ASYMF-UNV-L850-CD2-U	10041	66	153
8LBLED-LD4-10-ASYMF-UNV-L850-CD2-U	11317	75	150
8LBLED-LD4-12-ASYMF-UNV-L850-CD2-U	13574	91	149
8LBLED-LD4-14-ASYMF-UNV-L850-CD2-U	16085	112	144
8LBLED-LD4-16-ASYMF-UNV-L850-CD2-U	18041	127	142

Lumen Maintenance

Ambient Temperature	TM-21 Lumen Maintenance (60,000 hours)	Theoretical L70 (Hours)
25°C	> 83%	113,000

Shipping Data

Length	Wt.
4 ft.	8 lbs.
8 ft.	15 lbs.