

Ovation LED Direct/Indirect  
Recessed LED luminaire

**Metalux**



# Ovation LED Recessed LED luminaire

The **Ovation LED** series is a complete family of recessed direct/indirect luminaires dedicated to the latest solid-state lighting and driver technology for optimal performance and energy efficiency. Ovation LED's classic aesthetic allows for continuity in design when retrofitting spaces to LED. All components are located above the ceiling plane for a clean architectural appearance in the finished space. Carefully balanced design elements combine to provide an efficient and modern alternative to traditional general lighting. Ovation LED is an excellent choice for commercial office spaces, schools, hospitals, or retail merchandising areas.



## Construction

- Recessed: 1' x 4', 2' x 2' and 2' x 4'
- Depth: 6"
- Air venting option available
- cULus damp location / IC Rated / RoHS compliant
- Sustainable materials
- Five-year warranty

## Performance

- High-performance efficacy up to 109 lm/W
- Energy savings in excess of 60% compared to traditional fluorescent troffers
- Four Correlated Color Temperatures (3000K, 3500K, 4000K and 5000K) at a minimum CRI of 80
- 1' x 4': L91 @ 60,000 hrs.  
2' x 2': L90 @ 60,000 hrs.  
2' x 4': L89 @ 60,000 hrs.
- Binning: Per ANSI, 3-step MacAdam ellipse

## Options

- Multiple lumen packages in four CCTs
  - 1' x 4': 1800 and 2500
  - 2' x 2': 2000, 3000 and 4000
  - 2' x 4': 3000, 4000 and 5000
- Lens option – Metal perforated lens
- Universal (120V-277V) or 347V
- Emergency – EL7W and EL14W
- Surface mount field install kits
- Flex wiring configurations
- Chicago plenum rated version

## Control system compatibility

Ovation LED luminaires offer a range of connectivity options for code compliance, energy management and more using Cooper Lighting Solutions' advanced control systems. The Ovation includes 0-10V dimming drivers (1% - 100%) for use with wall dimmers, daylight dimming sensors or Cooper Lighting Solutions Room Controllers. Other options are available:

### System options:

- Wired:
  - Low-voltage dimming drivers (1%-100%) deliver installation savings and safety with the Distributed Low Voltage Power System.
  - DALI dimming drivers (10%-100% or 1%-100%) for complete digital energy management using Fifth Light addressable lighting controls.



- Wireless:
  - Enlighted tile mount sensor system provides wireless connectivity, fully configurable software for energy management and advanced Internet of Things (IoT) capabilities.

## Compliance and approvals





## Energy and performance

Select 2' x 4' Ovation LED SKUs			Popular fluorescent fixtures			Energy savings
Catalog number	Lumens*	Wattage	Fixture type	Lumens*	Wattage	
24RDI-50-UNV-L835-CD1-U	5067	50.3	Parabolic 332	5646	83.0	<b>-39%</b>
24RDI-40-UNV-L835-CD1-U	4097	39.6	Indirect Basket 332	4583	83.7	<b>-52%</b>
			Spec Dual Lens 228T5	4576	58.0	<b>-31%</b>
24RDI-30-UNV-L835-CD1-U	3132	28.7	Troffer 232	4310	52.0	<b>-44%</b>
			Indirect Basket 232	3873	72.0	<b>-60%</b>

  

Select 2' x 2' Ovation LED SKUs			Popular fluorescent fixtures			Energy savings
Catalog number	Lumens*	Wattage	Fixture type	Lumens*	Wattage	
22RDI-40-UNV-L835-CD1-U	4076	41.8	Indirect Basket 2BX40	4324	68.2	<b>-38%</b>
22RDI-30-UNV-L835-CD1-U	3032	30.1	Troffer 2U6T8	3862	52.1	<b>-42%</b>
22RDI-20-UNV-L835-CD1-U	2026	19.9	Troffer 317	2601	42.9	<b>-53%</b>
			Parabolic 317	2588	49.1	<b>-59%</b>
			Spec Dual Lens 214	2403	30.0	<b>-33%</b>

\*Lumens listed are delivered lumens.



**Lighting Product Lines**

Ametrix  
AtLite  
Corelite  
Ephesus  
Fail-Safe  
Halo  
Halo Commercial  
Invue  
io  
Iris  
Lumark  
Lumière  
McGraw-Edison  
Metalux  
MWS  
Neo-Ray  
Portfolio  
RSA  
Shaper  
Streetworks  
Sure-Lites

**Controls Product Lines**

Fifth Light Technology  
Greengate  
iLight (International Only)  
iLumin  
Zero 88

**Connected Lighting Systems**

Distributed Low-Voltage Power  
HALO Home  
iLumin Plus  
Enlighted  
WaveLinx  
Trellix



Cooper Lighting Solutions  
1121 Highway 74 South  
Peachtree City, GA 30269  
P: 770-486-4800  
[www.cooperlighting.com](http://www.cooperlighting.com)

Canada Sales  
5925 McLaughlin Road  
Mississauga, Ontario L5R 1B8  
P: 905-501-3000  
F: 905-501-3172

Cooper Lighting Solutions is a registered trademark.

All other trademarks are property of their respective owners.

Product availability, specifications, and compliances are subject to change without notice.

© 2020 Cooper Lighting Solutions  
All Rights Reserved  
Printed in USA  
Publication No. BR519035EN  
September 9, 2020 4:19 PM