


# EUROSTYLE COLLECTION

## SPECIFICATIONS


- 120-277V INPUT VOLTAGE, 50/60Hz
- CONSTANT CURRENT AT 700 MILLIAMPS
- DRIVER UL CLASS 2, POWER FACTOR > .90
- OPERATING TEMPERATURE -18°C (0°F) TO 40°C (104°F) (25°C NOMINAL)
- ESTIMATED 50,000 HRS L<sub>70</sub>\*
- THERMALLY PROTECTED LED ARRAY
- POWDERCOATED ALUMINUM BACK PAN
- MOLDED OF DURABLE NON-CORROSIVE UV RESISTANT PLASTICS
- WALL OR CEILING MOUNT
- UL/CUL LISTED FOR WET LOCATION
- STANDARD PACK QTY: 12




**SPJ362**



**SPJ361**



**SPJ363**



EXAMPLE # **SPJ361-L1800C-BFP**

STYLE #	SOURCE/WATTAGE	COLOR TEMP	BODY	DIFFUSER	OPTION
<b>SPJ361</b> = ROUND <b>SPJ362</b> = GRILL <b>SPJ363</b> = GRID	<b>L1800C</b> = 8 CREE LED ARRAY (14W) 22W POWER INPUT 1824 LUMENS <b>82 LUMENS PER WATT**</b>	4000K CRI = 74 (TYP)	<b>B</b> = BLACK <b>W</b> = WHITE	<b>F</b> = FROSTED	<b>P</b> = PHOTOCELL Photocells are only available for 120V applications

L1800C LED REPLACEMENT PARTS
<b>L18C-DC-700-08-R</b> = 8 CREE LED ARRAY
<b>IG1800-DMV-1</b> = LED DRIVER

\* DATA PER LM80/TM21 @ 1000MA AVAILABLE UPON REQUEST  
 \*\* ESTIMATED FOR LED SOURCE

For more information regarding SPJ Lighting's LED Fixtures and Custom Packaging please contact our sales department at **800-469-3637** or visit **www.spjlighting.com.com**



Specifications, design & components subject to change without notice. Printed in U.S.A. © 2012 SPJ Lighting Inc.

1203.1