

# 9312TO CHAMPAIGN SERIES

## **SPECIFICATIONS**

#### **GENERAL**


The \_\_\_\_\_ tall\* decorative post shall be aluminum, one-piece cast construction. The 18 <sup>1</sup>/<sub>4</sub>" wide octagonal cast aluminum base shall have flat sides with eight recessed panels in the base. The Model shall be Sternberg Lighting Number #9300TO or #9300TOR for candy cane pole. The pole shall be U.L. or E.T.L. listed in U.S. and Canada.

### CONSTRUCTION


The base shall have a large octagonal lower section designed with a recessed panels and terminated with three octagonal protruding rings. It shall taper into the shaft and gently transition into a flared top section. It shall be made of heavy wall, 356 alloy cast aluminum and be fully cast in one piece. It shall have a 1" thick floor cast as an integral part of the base.

### **INSTALLATION**

Four <sup>3</sup>/<sub>4</sub>" diameter, hot-dipped galvanized "L" type anchor bolts shall be provided with the post for anchorage. A door shall be provided for wiring and anchor bolt access. It shall be secured with tamper proof, stainless steel hardware. Post will be provided with a grounding stud mounted on the base floor opposite the access door.




\*\*See installation template for exact door position. Bolt circle dimensions may change on taller poles.



\*For candy cane poles insert \_\_\_\_\_AG ft (feet - above grade height). See diagram on reverse side.


# CHAMPAIGN SERIES

# POSTS / OPTIONS / POST CAPS



### **OPTIONS AVAILABLE**

### See Accessories Section for more options and information



## **POST CENTER CAPS** (If Required)



BCC-7 Ball Center Cap



SCC-7 Spiked Center Cap



SSCC-7 Side Spiked Center Cap



FCC-7 Finial Center Cap



TFCC-7 Tall Finial Center Cap



CAC-7 Cast Cap-Plain

