PRODUCT FEATURES



LAMPING

Provides support for long runs or runs with a changing cable drop. Offered for a range of drops and cable separations. Not field-cuttable. To run the system just beneath a surface transformer, use the 5" drop.

Kable Lite Rigid T Standoff



Kable Lite Rigid T Standoff

ORDERING INFORMATION

700KTSO	LENGTH (A)	CABLE SEPARATION	FINISH
	02 2.5"	03 3.50000	S SATIN NICKEL
	05 5"	05 5.50000	
		08 8.00000	

700KTSO	
JOB NAME	
NOTES	




KABLE LITE RIGID T STANDOFF

TECH LIGHTING

SPECIFICATIONS

HARDWARE MATERIAL			
SHADE MATERIAL			
NET WEIGHT	0.25 lbs		
HEIGHT	2.5in		
WIDTH	5.5in		
LENGTH	5.5in		
WET LISTED			
DAMP LISTED			
DRY LISTED			
GENERAL LISTING	ETL Listed		
INCLUDES			



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
INPUT VOLTAGE			OV	
DIMMING TYPE*				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**			1 Year	

 $^{* \ \, \}text{Dimming information available at} \, \underline{\text{www.techlighting.com/Downloads\#dimming}}$

T20/T24/JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with			
California Building Energy Efficiency			N/A
Standards 2016 Title 24 Part 6 / JA8.			
This product can be used to comply with			
California Appliance Efficiency Standards			N1/A
2016 Title 20 and may be shipped to and	ł		N/A
sold in California.			

 $^{^{*}}$ If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



^{**} Visit techlighting.com for specific warranty limitations and details.