## PRODUCT FEATURES



## LAMPING

Slimline anchors secure cables at one end of run (with turnbuckles at other end). Mount to wall or ceiling. 1.5" washer (included) is recommended for ceiling mount support. Pair.

Kable Lite Slimline Anchors



Kable Lite Slimline Anchors

## ORDERING INFORMATION

700PRTTO FINISH

S SATIN NICKEL

700PRTT0

JOB NAME
NOTES




# KABLE LITE SLIMLINE ANCHORS

# TECH LIGHTING

# **SPECIFICATIONS**

HARDWARE MATERIAL		
SHADE MATERIAL		
NET WEIGHT	0.15 lbs	
HEIGHT	lin	
WIDTH	1.5in	
LENGTH	lin	
WET LISTED		
DAMP LISTED		
DRY LISTED		
GENERAL LISTING	ETL Listed	
INCLUDES		



## LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
INPUT VOLTAGE			OV	
DIMMING TYPE*				
ССТ				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**			1 Year	

 $<sup>* \ \, \</sup>text{Dimming information available at} \, \underline{\text{www.techlighting.com/Downloads\#dimming}}$ 

# T20/T24/JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with			
California Building Energy Efficiency			N/A
Standards 2016 Title 24 Part 6 / JA8.			
This product can be used to comply with			
California Appliance Efficiency Standards			N1/A
2016 Title 20 and may be shipped to and	ł		N/A
sold in California.			

<sup>\*</sup> If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



<sup>\*\*</sup> Visit techlighting.com for specific warranty limitations and details.